

Product Guide

GOLD LABEL® Industrial Banded



GOLD LABEL®




FIND
YOUR
PART
NOW





MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded - Table of Contents



V-Belt Banded


GOLD LABEL

A-B-C-D

GOLD LABEL Banded Classical

Product Description3

Size List4



V-Belt Banded



GOLD LABEL

3V-5V-8V

GOLD LABEL Banded Narrow

Product Description38

Size List39



V-Belt Banded


GOLD LABEL

SPZ-SPA-SPB-SPC

GOLD LABEL Banded Wedge

Product Description51

Size List52



V-Belt Banded



GOLD LABEL

BX-CX

GOLD LABEL Banded X Classical

Product Description65

Size List66



V-Belt Banded



GOLD LABEL

3VX-5VX

GOLD LABEL Banded X Narrow

Product Description69

Size List70



V-Belt Banded

GOLD LABEL

XPZ-XPA-XPB

GOLD LABEL Banded X Wedge


Product Description75

Size List76



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical



V-Belt Banded

GOLD LABEL®



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

V-Belt

Part Number Description: **2/B120GL**

2/: Number of ribs

B: Profile

120: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, Rubber Impregnated

- Abrasion, wear and oil resistance
- Prevents vibrations and belt turn-over

Fabric Cover: PET/Cotton, Rubber Impregnated

- Abrasion, wear and oil resistance
- Static conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber Blend

- High resistance to bending stress
- Superior oil and heat resistance
- Temperature range: -31°F (-35°C) to 160°F (70°C)

Markets and Applications:


Designed for high horsepower and shock load applications, these industrial banded belts are primarily employed on applications where multiple belts have the tendency to vibrate, turn over or come off pulleys when subjected to fluctuating load tensions and high horsepower.

The Dayco GOLD LABEL industrial banded belt is available in both wrapped molded construction and raw edge versions and provides the same oil and heat resistant characteristics as the Dayco GOLD LABEL single belts with the addition of a fabric rubber top band for multiple belt stability.



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/A58GL	2	A	1473	58.00	0.54	1.19
2/A59GL	2	A	1499	59.00	0.55	1.21
2/A60GL	2	A	1524	60.00	0.56	1.23
2/A62GL	2	A	1575	62.00	0.57	1.27
2/A64GL	2	A	1626	64.00	0.59	1.31
2/A65GL	2	A	1651	65.00	0.60	1.33
2/A66GL	2	A	1676	66.00	0.61	1.35
2/A67GL	2	A	1702	67.00	0.62	1.37
2/A68GL	2	A	1727	68.00	0.63	1.39
2/A70GL	2	A	1778	70.00	0.65	1.43
2/A71GL	2	A	1803	71.00	0.66	1.45
2/A74GL	2	A	1880	74.00	0.69	1.51
2/A75GL	2	A	1905	75.00	0.70	1.53
2/A77GL	2	A	1956	77.00	0.71	1.57
2/A78GL	2	A	1981	78.00	0.72	1.59
2/A79GL	2	A	2007	79.00	0.73	1.61
2/A80GL	2	A	2032	80.00	0.74	1.64
2/A81GL	2	A	2057	81.00	0.75	1.66
2/A83GL	2	A	2108	83.00	0.77	1.70
2/A85GL	2	A	2159	85.00	0.79	1.74
2/A88GL	2	A	2235	88.00	0.82	1.80
2/A90GL	2	A	2286	90.00	0.83	1.84
2/A92GL	2	A	2337	92.00	0.85	1.88
2/A96GL	2	A	2438	96.00	0.89	1.96
2/A98GL	2	A	2489	98.00	0.91	2.00
2/A100GL	2	A	2540	100.00	0.93	2.04
2/A104GL	2	A	2642	104.00	0.96	2.13
2/A105GL	2	A	2667	105.00	0.97	2.15
2/A110GL	2	A	2794	110.00	1.02	2.25
2/A112GL	2	A	2845	112.00	1.04	2.29
2/A120GL	2	A	3048	120.00	1.11	2.45
2/A128GL	2	A	3251	128.00	1.19	2.62



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/A136GL	2	A	3454	136.00	1.26	2.78
2/A144GL	2	A	3658	144.00	1.34	2.94
2/A158GL	2	A	4013	158.00	1.46	3.23
2/A167GL	2	A	4242	167.00	1.55	3.41
2/A173GL	2	A	4394	173.00	1.60	3.54
2/A180GL	2	A	4572	180.00	1.67	3.68
2/A187GL	2	A	4750	187.00	1.73	3.82
3/A58GL	3	A	1473	58.00	0.81	1.78
3/A59GL	3	A	1499	59.00	0.82	1.81
3/A60GL	3	A	1524	60.00	0.83	1.84
3/A62GL	3	A	1575	62.00	0.86	1.90
3/A64GL	3	A	1626	64.00	0.89	1.96
3/A65GL	3	A	1651	65.00	0.90	1.99
3/A66GL	3	A	1676	66.00	0.92	2.02
3/A67GL	3	A	1702	67.00	0.93	2.05
3/A68GL	3	A	1727	68.00	0.95	2.08
3/A70GL	3	A	1778	70.00	0.97	2.15
3/A71GL	3	A	1803	71.00	0.99	2.18
3/A74GL	3	A	1880	74.00	1.03	2.27
3/A75GL	3	A	1905	75.00	1.04	2.30
3/A77GL	3	A	1956	77.00	1.07	2.36
3/A78GL	3	A	1981	78.00	1.08	2.39
3/A79GL	3	A	2007	79.00	1.10	2.42
3/A80GL	3	A	2032	80.00	1.11	2.45
3/A81GL	3	A	2057	81.00	1.13	2.48
3/A83GL	3	A	2108	83.00	1.15	2.54
3/A85GL	3	A	2159	85.00	1.18	2.61
3/A88GL	3	A	2235	88.00	1.22	2.70
3/A90GL	3	A	2286	90.00	1.25	2.76
3/A92GL	3	A	2337	92.00	1.28	2.82
3/A96GL	3	A	2438	96.00	1.34	2.94
3/A98GL	3	A	2489	98.00	1.36	3.00



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/A100GL	3	A	2540	100.00	1.39	3.07
3/A104GL	3	A	2642	104.00	1.45	3.19
3/A105GL	3	A	2667	105.00	1.46	3.22
3/A110GL	3	A	2794	110.00	1.53	3.37
3/A112GL	3	A	2845	112.00	1.56	3.43
3/A120GL	3	A	3048	120.00	1.67	3.68
3/A128GL	3	A	3251	128.00	1.78	3.92
3/A136GL	3	A	3454	136.00	1.89	4.17
3/A144GL	3	A	3658	144.00	2.00	4.42
3/A158GL	3	A	4013	158.00	2.20	4.84
3/A167GL	3	A	4242	167.00	2.32	5.12
3/A173GL	3	A	4394	173.00	2.41	5.30
3/A180GL	3	A	4572	180.00	2.50	5.52
3/A187GL	3	A	4750	187.00	2.60	5.73
4/A58GL	4	A	1473	58.00	1.08	2.37
4/A59GL	4	A	1499	59.00	1.09	2.41
4/A60GL	4	A	1524	60.00	1.11	2.45
4/A62GL	4	A	1575	62.00	1.15	2.53
4/A64GL	4	A	1626	64.00	1.19	2.62
4/A65GL	4	A	1651	65.00	1.21	2.66
4/A66GL	4	A	1676	66.00	1.22	2.70
4/A67GL	4	A	1702	67.00	1.24	2.74
4/A68GL	4	A	1727	68.00	1.26	2.78
4/A70GL	4	A	1778	70.00	1.30	2.86
4/A71GL	4	A	1803	71.00	1.32	2.90
4/A74GL	4	A	1880	74.00	1.37	3.03
4/A75GL	4	A	1905	75.00	1.39	3.07
4/A77GL	4	A	1956	77.00	1.43	3.15
4/A78GL	4	A	1981	78.00	1.45	3.19
4/A79GL	4	A	2007	79.00	1.46	3.23
4/A80GL	4	A	2032	80.00	1.48	3.27
4/A81GL	4	A	2057	81.00	1.50	3.31



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/A83GL	4	A	2108	83.00	1.54	3.39
4/A85GL	4	A	2159	85.00	1.58	3.47
4/A88GL	4	A	2235	88.00	1.63	3.60
4/A90GL	4	A	2286	90.00	1.67	3.68
4/A92GL	4	A	2337	92.00	1.71	3.76
4/A96GL	4	A	2438	96.00	1.78	3.92
4/A98GL	4	A	2489	98.00	1.82	4.01
4/A100GL	4	A	2540	100.00	1.85	4.09
4/A104GL	4	A	2642	104.00	1.93	4.25
4/A105GL	4	A	2667	105.00	1.95	4.29
4/A110GL	4	A	2794	110.00	2.04	4.50
4/A112GL	4	A	2845	112.00	2.08	4.58
4/A120GL	4	A	3048	120.00	2.23	4.91
4/A128GL	4	A	3251	128.00	2.37	5.23
4/A136GL	4	A	3454	136.00	2.52	5.56
4/A144GL	4	A	3658	144.00	2.67	5.89
4/A158GL	4	A	4013	158.00	2.93	6.46
4/A167GL	4	A	4242	167.00	3.10	6.83
4/A173GL	4	A	4394	173.00	3.21	7.07
4/A180GL	4	A	4572	180.00	3.34	7.36
4/A187GL	4	A	4750	187.00	3.47	7.64
5/A58GL	5	A	1473	58.00	1.34	2.96
5/A59GL	5	A	1499	59.00	1.37	3.01
5/A60GL	5	A	1524	60.00	1.39	3.07
5/A62GL	5	A	1575	62.00	1.44	3.17
5/A64GL	5	A	1626	64.00	1.48	3.27
5/A65GL	5	A	1651	65.00	1.51	3.32
5/A66GL	5	A	1676	66.00	1.53	3.37
5/A67GL	5	A	1702	67.00	1.55	3.42
5/A68GL	5	A	1727	68.00	1.58	3.47
5/A70GL	5	A	1778	70.00	1.62	3.58
5/A71GL	5	A	1803	71.00	1.65	3.63



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/A74GL	5	A	1880	74.00	1.72	3.78
5/A75GL	5	A	1905	75.00	1.74	3.83
5/A77GL	5	A	1956	77.00	1.78	3.93
5/A78GL	5	A	1981	78.00	1.81	3.99
5/A79GL	5	A	2007	79.00	1.83	4.04
5/A80GL	5	A	2032	80.00	1.85	4.09
5/A81GL	5	A	2057	81.00	1.88	4.14
5/A83GL	5	A	2108	83.00	1.92	4.24
5/A85GL	5	A	2159	85.00	1.97	4.34
5/A88GL	5	A	2235	88.00	2.04	4.50
5/A90GL	5	A	2286	90.00	2.09	4.60
5/A92GL	5	A	2337	92.00	2.13	4.70
5/A96GL	5	A	2438	96.00	2.23	4.91
5/A98GL	5	A	2489	98.00	2.27	5.01
5/A100GL	5	A	2540	100.00	2.32	5.11
5/A104GL	5	A	2642	104.00	2.41	5.31
5/A105GL	5	A	2667	105.00	2.43	5.37
5/A110GL	5	A	2794	110.00	2.55	5.62
5/A112GL	5	A	2845	112.00	2.60	5.72
5/A120GL	5	A	3048	120.00	2.78	6.13
5/A128GL	5	A	3251	128.00	2.97	6.54
5/A136GL	5	A	3454	136.00	3.15	6.95
5/A144GL	5	A	3658	144.00	3.34	7.36
5/A158GL	5	A	4013	158.00	3.66	8.07
5/A167GL	5	A	4242	167.00	3.87	8.53
5/A173GL	5	A	4394	173.00	4.01	8.84
5/A180GL	5	A	4572	180.00	4.17	9.20
5/A187GL	5	A	4750	187.00	4.33	9.56
19/A58GL	19	A	1473	58.00	5.11	11.26
19/A59GL	19	A	1499	59.00	5.20	11.46
19/A60GL	19	A	1524	60.00	5.28	11.65
19/A62GL	19	A	1575	62.00	5.46	12.04



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
19/A64GL	19	A	1626	64.00	5.64	12.43
19/A65GL	19	A	1651	65.00	5.73	12.62
19/A66GL	19	A	1676	66.00	5.81	12.82
19/A67GL	19	A	1702	67.00	5.90	13.01
19/A68GL	19	A	1727	68.00	5.99	13.20
19/A70GL	19	A	1778	70.00	6.17	13.59
19/A71GL	19	A	1803	71.00	6.25	13.79
19/A74GL	19	A	1880	74.00	6.52	14.37
19/A75GL	19	A	1905	75.00	6.61	14.56
19/A77GL	19	A	1956	77.00	6.78	14.95
19/A78GL	19	A	1981	78.00	6.87	15.15
19/A79GL	19	A	2007	79.00	6.96	15.34
19/A80GL	19	A	2032	80.00	7.05	15.53
19/A81GL	19	A	2057	81.00	7.13	15.73
19/A83GL	19	A	2108	83.00	7.31	16.12
19/A85GL	19	A	2159	85.00	7.49	16.51
19/A88GL	19	A	2235	88.00	7.75	17.09
19/A90GL	19	A	2286	90.00	7.93	17.48
19/A92GL	19	A	2337	92.00	8.10	17.86
19/A96GL	19	A	2438	96.00	8.46	18.64
19/A98GL	19	A	2489	98.00	8.63	19.03
19/A100GL	19	A	2540	100.00	8.81	19.42
19/A104GL	19	A	2642	104.00	9.16	20.20
19/A105GL	19	A	2667	105.00	9.25	20.39
19/A110GL	19	A	2794	110.00	9.69	21.36
19/A112GL	19	A	2845	112.00	9.86	21.75
19/A120GL	19	A	3048	120.00	10.57	23.30
19/A128GL	19	A	3251	128.00	11.27	24.86
19/A136GL	19	A	3454	136.00	11.98	26.41
19/A144GL	19	A	3658	144.00	12.68	27.96
19/A158GL	19	A	4013	158.00	13.92	30.68
19/A167GL	19	A	4242	167.00	14.71	32.43



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
19/A173GL	19	A	4394	173.00	15.24	33.59
19/A180GL	19	A	4572	180.00	15.85	34.95
19/A187GL	19	A	4750	187.00	16.47	36.31
2/B56GL	2	B	1422	56.00	0.73	1.61
2/B57GL	2	B	1448	57.00	0.74	1.64
2/B58GL	2	B	1473	58.00	0.76	1.67
2/B59GL	2	B	1499	59.00	0.77	1.69
2/B60GL	2	B	1524	60.00	0.78	1.72
2/B61GL	2	B	1549	61.00	0.79	1.75
2/B62GL	2	B	1575	62.00	0.81	1.78
2/B63GL	2	B	1600	63.00	0.82	1.81
2/B64GL	2	B	1626	64.00	0.83	1.84
2/B65GL	2	B	1651	65.00	0.85	1.87
2/B66GL	2	B	1676	66.00	0.86	1.90
2/B67GL	2	B	1702	67.00	0.87	1.92
2/B68GL	2	B	1727	68.00	0.89	1.95
2/B70GL	2	B	1778	70.00	0.91	2.01
2/B71GL	2	B	1803	71.00	0.93	2.04
2/B72GL	2	B	1829	72.00	0.94	2.07
2/B73GL	2	B	1854	73.00	0.95	2.10
2/B74GL	2	B	1880	74.00	0.96	2.13
2/B75GL	2	B	1905	75.00	0.98	2.15
2/B77GL	2	B	1956	77.00	1.00	2.21
2/B78GL	2	B	1981	78.00	1.02	2.24
2/B79GL	2	B	2007	79.00	1.03	2.27
2/B80GL	2	B	2032	80.00	1.04	2.30
2/B81GL	2	B	2057	81.00	1.06	2.33
2/B82GL	2	B	2083	82.00	1.07	2.36
2/B83GL	2	B	2108	83.00	1.08	2.38
2/B84GL	2	B	2134	84.00	1.09	2.41
2/B85GL	2	B	2159	85.00	1.11	2.44
2/B86GL	2	B	2184	86.00	1.12	2.47



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/B87GL	2	B	2210	87.00	1.13	2.50
2/B88GL	2	B	2235	88.00	1.15	2.53
2/B90GL	2	B	2286	90.00	1.17	2.59
2/B91GL	2	B	2311	91.00	1.19	2.61
2/B92GL	2	B	2337	92.00	1.20	2.64
2/B93GL	2	B	2362	93.00	1.21	2.67
2/B94.5GL	2	B	2400	94.50	1.23	2.71
2/B95GL	2	B	2413	95.00	1.24	2.73
2/B96GL	2	B	2438	96.00	1.25	2.76
2/B97GL	2	B	2464	97.00	1.26	2.79
2/B98GL	2	B	2489	98.00	1.28	2.81
2/B99GL	2	B	2515	99.00	1.29	2.84
2/B100GL	2	B	2540	100.00	1.30	2.87
2/B102GL	2	B	2591	102.00	1.33	2.93
2/B103GL	2	B	2616	103.00	1.34	2.96
2/B104GL	2	B	2642	104.00	1.35	2.99
2/B105GL	2	B	2667	105.00	1.37	3.02
2/B106GL	2	B	2692	106.00	1.38	3.04
2/B108GL	2	B	2743	108.00	1.41	3.10
2/B109GL	2	B	2769	109.00	1.42	3.13
2/B110GL	2	B	2794	110.00	1.43	3.16
2/B112GL	2	B	2845	112.00	1.46	3.22
2/B113GL	2	B	2870	113.00	1.47	3.25
2/B114GL	2	B	2896	114.00	1.49	3.27
2/B115GL	2	B	2921	115.00	1.50	3.30
2/B116GL	2	B	2946	116.00	1.51	3.33
2/B118GL	2	B	2997	118.00	1.54	3.39
2/B120GL	2	B	3048	120.00	1.56	3.45
2/B124GL	2	B	3150	124.00	1.62	3.56
2/B128GL	2	B	3251	128.00	1.67	3.68
2/B130GL	2	B	3302	130.00	1.69	3.73
2/B132GL	2	B	3353	132.00	1.72	3.79



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/B133GL	2	B	3378	133.00	1.73	3.82
2/B136GL	2	B	3454	136.00	1.77	3.91
2/B138GL	2	B	3505	138.00	1.80	3.96
2/B139GL	2	B	3531	139.00	1.81	3.99
2/B140GL	2	B	3556	140.00	1.82	4.02
2/B141GL	2	B	3581	141.00	1.84	4.05
2/B144GL	2	B	3658	144.00	1.88	4.14
2/B146GL	2	B	3708	146.00	1.90	4.19
2/B148GL	2	B	3759	148.00	1.93	4.25
2/B150GL	2	B	3810	150.00	1.95	4.31
2/B154GL	2	B	3912	154.00	2.01	4.42
2/B158GL	2	B	4013	158.00	2.06	4.54
2/B160GL	2	B	4064	160.00	2.08	4.60
2/B162GL	2	B	4115	162.00	2.11	4.65
2/B167GL	2	B	4242	167.00	2.18	4.80
2/B168GL	2	B	4267	168.00	2.19	4.83
2/B173GL	2	B	4394	173.00	2.25	4.97
2/B177GL	2	B	4496	177.00	2.31	5.08
2/B180GL	2	B	4572	180.00	2.35	5.17
2/B185GL	2	B	4699	185.00	2.41	5.31
2/B187GL	2	B	4750	187.00	2.44	5.37
2/B190GL	2	B	4826	190.00	2.48	5.46
2/B195GL	2	B	4953	195.00	2.54	5.60
2/B197GL	2	B	5004	197.00	2.57	5.66
2/B208GL	2	B	5283	208.00	2.71	5.97
2/B210GL	2	B	5334	210.00	2.74	6.03
2/B218GL	2	B	5537	218.00	2.84	6.26
2/B220GL	2	B	5588	220.00	2.87	6.32
2/B225GL	2	B	5715	225.00	2.93	6.46
2/B240GL	2	B	6096	240.00	3.13	6.89
2/B255GL	2	B	6477	255.00	3.32	7.32
2/B270GL	2	B	6858	270.00	3.52	7.76



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/B300GL	2	B	7620	300.00	3.91	8.62
2/B315GL	2	B	8001	315.00	4.10	9.05
3/B56GL	3	B	1422	56.00	1.09	2.41
3/B57GL	3	B	1448	57.00	1.11	2.46
3/B58GL	3	B	1473	58.00	1.13	2.50
3/B59GL	3	B	1499	59.00	1.15	2.54
3/B60GL	3	B	1524	60.00	1.17	2.59
3/B61GL	3	B	1549	61.00	1.19	2.63
3/B62GL	3	B	1575	62.00	1.21	2.67
3/B63GL	3	B	1600	63.00	1.23	2.71
3/B64GL	3	B	1626	64.00	1.25	2.76
3/B65GL	3	B	1651	65.00	1.27	2.80
3/B66GL	3	B	1676	66.00	1.29	2.84
3/B67GL	3	B	1702	67.00	1.31	2.89
3/B68GL	3	B	1727	68.00	1.33	2.93
3/B70GL	3	B	1778	70.00	1.37	3.02
3/B71GL	3	B	1803	71.00	1.39	3.06
3/B72GL	3	B	1829	72.00	1.41	3.10
3/B73GL	3	B	1854	73.00	1.43	3.15
3/B74GL	3	B	1880	74.00	1.45	3.19
3/B75GL	3	B	1905	75.00	1.47	3.23
3/B77GL	3	B	1956	77.00	1.50	3.32
3/B78GL	3	B	1981	78.00	1.52	3.36
3/B79GL	3	B	2007	79.00	1.54	3.40
3/B80GL	3	B	2032	80.00	1.56	3.45
3/B81GL	3	B	2057	81.00	1.58	3.49
3/B82GL	3	B	2083	82.00	1.60	3.53
3/B83GL	3	B	2108	83.00	1.62	3.58
3/B84GL	3	B	2134	84.00	1.64	3.62
3/B85GL	3	B	2159	85.00	1.66	3.66
3/B86GL	3	B	2184	86.00	1.68	3.71
3/B87GL	3	B	2210	87.00	1.70	3.75



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/B88GL	3	B	2235	88.00	1.72	3.79
3/B90GL	3	B	2286	90.00	1.76	3.88
3/B91GL	3	B	2311	91.00	1.78	3.92
3/B92GL	3	B	2337	92.00	1.80	3.96
3/B93GL	3	B	2362	93.00	1.82	4.01
3/B94.5GL	3	B	2400	94.50	1.85	4.07
3/B95GL	3	B	2413	95.00	1.86	4.09
3/B96GL	3	B	2438	96.00	1.88	4.14
3/B97GL	3	B	2464	97.00	1.90	4.18
3/B98GL	3	B	2489	98.00	1.92	4.22
3/B99GL	3	B	2515	99.00	1.93	4.27
3/B100GL	3	B	2540	100.00	1.95	4.31
3/B102GL	3	B	2591	102.00	1.99	4.39
3/B103GL	3	B	2616	103.00	2.01	4.44
3/B104GL	3	B	2642	104.00	2.03	4.48
3/B105GL	3	B	2667	105.00	2.05	4.52
3/B106GL	3	B	2692	106.00	2.07	4.57
3/B108GL	3	B	2743	108.00	2.11	4.65
3/B109GL	3	B	2769	109.00	2.13	4.70
3/B110GL	3	B	2794	110.00	2.15	4.74
3/B112GL	3	B	2845	112.00	2.19	4.83
3/B113GL	3	B	2870	113.00	2.21	4.87
3/B114GL	3	B	2896	114.00	2.23	4.91
3/B115GL	3	B	2921	115.00	2.25	4.95
3/B116GL	3	B	2946	116.00	2.27	5.00
3/B118GL	3	B	2997	118.00	2.31	5.08
3/B120GL	3	B	3048	120.00	2.35	5.17
3/B124GL	3	B	3150	124.00	2.42	5.34
3/B128GL	3	B	3251	128.00	2.50	5.51
3/B130GL	3	B	3302	130.00	2.54	5.60
3/B132GL	3	B	3353	132.00	2.58	5.69
3/B133GL	3	B	3378	133.00	2.60	5.73



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/B136GL	3	B	3454	136.00	2.66	5.86
3/B138GL	3	B	3505	138.00	2.70	5.95
3/B139GL	3	B	3531	139.00	2.72	5.99
3/B140GL	3	B	3556	140.00	2.74	6.03
3/B141GL	3	B	3581	141.00	2.76	6.07
3/B144GL	3	B	3658	144.00	2.81	6.20
3/B146GL	3	B	3708	146.00	2.85	6.29
3/B148GL	3	B	3759	148.00	2.89	6.38
3/B150GL	3	B	3810	150.00	2.93	6.46
3/B154GL	3	B	3912	154.00	3.01	6.64
3/B158GL	3	B	4013	158.00	3.09	6.81
3/B160GL	3	B	4064	160.00	3.13	6.89
3/B162GL	3	B	4115	162.00	3.17	6.98
3/B167GL	3	B	4242	167.00	3.26	7.20
3/B168GL	3	B	4267	168.00	3.28	7.24
3/B173GL	3	B	4394	173.00	3.38	7.45
3/B177GL	3	B	4496	177.00	3.46	7.63
3/B180GL	3	B	4572	180.00	3.52	7.76
3/B185GL	3	B	4699	185.00	3.62	7.97
3/B187GL	3	B	4750	187.00	3.65	8.06
3/B190GL	3	B	4826	190.00	3.71	8.19
3/B195GL	3	B	4953	195.00	3.81	8.40
3/B197GL	3	B	5004	197.00	3.85	8.49
3/B208GL	3	B	5283	208.00	4.06	8.96
3/B210GL	3	B	5334	210.00	4.10	9.05
3/B218GL	3	B	5537	218.00	4.26	9.39
3/B220GL	3	B	5588	220.00	4.30	9.48
3/B225GL	3	B	5715	225.00	4.40	9.69
3/B240GL	3	B	6096	240.00	4.69	10.34
3/B255GL	3	B	6477	255.00	4.98	10.99
3/B270GL	3	B	6858	270.00	5.28	11.63
3/B300GL	3	B	7620	300.00	5.86	12.93



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/B315GL	3	B	8001	315.00	6.16	13.57
4/B56GL	4	B	1422	56.00	1.46	3.22
4/B57GL	4	B	1448	57.00	1.49	3.27
4/B58GL	4	B	1473	58.00	1.51	3.33
4/B59GL	4	B	1499	59.00	1.54	3.39
4/B60GL	4	B	1524	60.00	1.56	3.45
4/B61GL	4	B	1549	61.00	1.59	3.50
4/B62GL	4	B	1575	62.00	1.62	3.56
4/B63GL	4	B	1600	63.00	1.64	3.62
4/B64GL	4	B	1626	64.00	1.67	3.68
4/B65GL	4	B	1651	65.00	1.69	3.73
4/B66GL	4	B	1676	66.00	1.72	3.79
4/B67GL	4	B	1702	67.00	1.75	3.85
4/B68GL	4	B	1727	68.00	1.77	3.91
4/B70GL	4	B	1778	70.00	1.82	4.02
4/B71GL	4	B	1803	71.00	1.85	4.08
4/B72GL	4	B	1829	72.00	1.88	4.14
4/B73GL	4	B	1854	73.00	1.90	4.19
4/B74GL	4	B	1880	74.00	1.93	4.25
4/B75GL	4	B	1905	75.00	1.95	4.31
4/B77GL	4	B	1956	77.00	2.01	4.42
4/B78GL	4	B	1981	78.00	2.03	4.48
4/B79GL	4	B	2007	79.00	2.06	4.54
4/B80GL	4	B	2032	80.00	2.08	4.60
4/B81GL	4	B	2057	81.00	2.11	4.65
4/B82GL	4	B	2083	82.00	2.14	4.71
4/B83GL	4	B	2108	83.00	2.16	4.77
4/B84GL	4	B	2134	84.00	2.19	4.83
4/B85GL	4	B	2159	85.00	2.21	4.88
4/B86GL	4	B	2184	86.00	2.24	4.94
4/B87GL	4	B	2210	87.00	2.27	5.00
4/B88GL	4	B	2235	88.00	2.29	5.06



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/B90GL	4	B	2286	90.00	2.35	5.17
4/B91GL	4	B	2311	91.00	2.37	5.23
4/B92GL	4	B	2337	92.00	2.40	5.29
4/B93GL	4	B	2362	93.00	2.42	5.34
4/B94.5GL	4	B	2400	94.50	2.46	5.43
4/B95GL	4	B	2413	95.00	2.48	5.46
4/B96GL	4	B	2438	96.00	2.50	5.51
4/B97GL	4	B	2464	97.00	2.53	5.57
4/B98GL	4	B	2489	98.00	2.55	5.63
4/B99GL	4	B	2515	99.00	2.58	5.69
4/B100GL	4	B	2540	100.00	2.61	5.74
4/B102GL	4	B	2591	102.00	2.66	5.86
4/B103GL	4	B	2616	103.00	2.68	5.92
4/B104GL	4	B	2642	104.00	2.71	5.97
4/B105GL	4	B	2667	105.00	2.74	6.03
4/B106GL	4	B	2692	106.00	2.76	6.09
4/B108GL	4	B	2743	108.00	2.81	6.20
4/B109GL	4	B	2769	109.00	2.84	6.26
4/B110GL	4	B	2794	110.00	2.87	6.32
4/B112GL	4	B	2845	112.00	2.92	6.43
4/B113GL	4	B	2870	113.00	2.94	6.49
4/B114GL	4	B	2896	114.00	2.97	6.55
4/B115GL	4	B	2921	115.00	3.00	6.61
4/B116GL	4	B	2946	116.00	3.02	6.66
4/B118GL	4	B	2997	118.00	3.07	6.78
4/B120GL	4	B	3048	120.00	3.13	6.89
4/B124GL	4	B	3150	124.00	3.23	7.12
4/B128GL	4	B	3251	128.00	3.34	7.35
4/B130GL	4	B	3302	130.00	3.39	7.47
4/B132GL	4	B	3353	132.00	3.44	7.58
4/B133GL	4	B	3378	133.00	3.47	7.64
4/B136GL	4	B	3454	136.00	3.54	7.81



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/B138GL	4	B	3505	138.00	3.60	7.93
4/B139GL	4	B	3531	139.00	3.62	7.99
4/B140GL	4	B	3556	140.00	3.65	8.04
4/B141GL	4	B	3581	141.00	3.67	8.10
4/B144GL	4	B	3658	144.00	3.75	8.27
4/B146GL	4	B	3708	146.00	3.80	8.39
4/B148GL	4	B	3759	148.00	3.86	8.50
4/B150GL	4	B	3810	150.00	3.91	8.62
4/B154GL	4	B	3912	154.00	4.01	8.85
4/B158GL	4	B	4013	158.00	4.12	9.08
4/B160GL	4	B	4064	160.00	4.17	9.19
4/B162GL	4	B	4115	162.00	4.22	9.31
4/B167GL	4	B	4242	167.00	4.35	9.59
4/B168GL	4	B	4267	168.00	4.38	9.65
4/B173GL	4	B	4394	173.00	4.51	9.94
4/B177GL	4	B	4496	177.00	4.61	10.17
4/B180GL	4	B	4572	180.00	4.69	10.34
4/B185GL	4	B	4699	185.00	4.82	10.63
4/B187GL	4	B	4750	187.00	4.87	10.74
4/B190GL	4	B	4826	190.00	4.95	10.91
4/B195GL	4	B	4953	195.00	5.08	11.20
4/B197GL	4	B	5004	197.00	5.13	11.32
4/B208GL	4	B	5283	208.00	5.42	11.95
4/B210GL	4	B	5334	210.00	5.47	12.06
4/B218GL	4	B	5537	218.00	5.68	12.52
4/B220GL	4	B	5588	220.00	5.73	12.64
4/B225GL	4	B	5715	225.00	5.86	12.93
4/B240GL	4	B	6096	240.00	6.25	13.79
4/B255GL	4	B	6477	255.00	6.64	14.65
4/B270GL	4	B	6858	270.00	7.04	15.51
4/B300GL	4	B	7620	300.00	7.82	17.23
4/B315GL	4	B	8001	315.00	8.21	18.10



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/B56GL	5	B	1422	56.00	1.82	4.02
5/B57GL	5	B	1448	57.00	1.86	4.09
5/B58GL	5	B	1473	58.00	1.89	4.16
5/B59GL	5	B	1499	59.00	1.92	4.24
5/B60GL	5	B	1524	60.00	1.95	4.31
5/B61GL	5	B	1549	61.00	1.99	4.38
5/B62GL	5	B	1575	62.00	2.02	4.45
5/B63GL	5	B	1600	63.00	2.05	4.52
5/B64GL	5	B	1626	64.00	2.08	4.60
5/B65GL	5	B	1651	65.00	2.12	4.67
5/B66GL	5	B	1676	66.00	2.15	4.74
5/B67GL	5	B	1702	67.00	2.18	4.81
5/B68GL	5	B	1727	68.00	2.21	4.88
5/B70GL	5	B	1778	70.00	2.28	5.03
5/B71GL	5	B	1803	71.00	2.31	5.10
5/B72GL	5	B	1829	72.00	2.35	5.17
5/B73GL	5	B	1854	73.00	2.38	5.24
5/B74GL	5	B	1880	74.00	2.41	5.31
5/B75GL	5	B	1905	75.00	2.44	5.39
5/B77GL	5	B	1956	77.00	2.51	5.53
5/B78GL	5	B	1981	78.00	2.54	5.60
5/B79GL	5	B	2007	79.00	2.57	5.67
5/B80GL	5	B	2032	80.00	2.61	5.74
5/B81GL	5	B	2057	81.00	2.64	5.82
5/B82GL	5	B	2083	82.00	2.67	5.89
5/B83GL	5	B	2108	83.00	2.70	5.96
5/B84GL	5	B	2134	84.00	2.74	6.03
5/B85GL	5	B	2159	85.00	2.77	6.10
5/B86GL	5	B	2184	86.00	2.80	6.18
5/B87GL	5	B	2210	87.00	2.83	6.25
5/B88GL	5	B	2235	88.00	2.87	6.32
5/B90GL	5	B	2286	90.00	2.93	6.46



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/B91GL	5	B	2311	91.00	2.96	6.53
5/B92GL	5	B	2337	92.00	3.00	6.61
5/B93GL	5	B	2362	93.00	3.03	6.68
5/B94.5GL	5	B	2400	94.50	3.08	6.79
5/B95GL	5	B	2413	95.00	3.09	6.82
5/B96GL	5	B	2438	96.00	3.13	6.89
5/B97GL	5	B	2464	97.00	3.16	6.97
5/B98GL	5	B	2489	98.00	3.19	7.04
5/B99GL	5	B	2515	99.00	3.22	7.11
5/B100GL	5	B	2540	100.00	3.26	7.18
5/B102GL	5	B	2591	102.00	3.32	7.32
5/B103GL	5	B	2616	103.00	3.35	7.40
5/B104GL	5	B	2642	104.00	3.39	7.47
5/B105GL	5	B	2667	105.00	3.42	7.54
5/B106GL	5	B	2692	106.00	3.45	7.61
5/B108GL	5	B	2743	108.00	3.52	7.76
5/B109GL	5	B	2769	109.00	3.55	7.83
5/B110GL	5	B	2794	110.00	3.58	7.90
5/B112GL	5	B	2845	112.00	3.65	8.04
5/B113GL	5	B	2870	113.00	3.68	8.11
5/B114GL	5	B	2896	114.00	3.71	8.19
5/B115GL	5	B	2921	115.00	3.75	8.26
5/B116GL	5	B	2946	116.00	3.78	8.33
5/B118GL	5	B	2997	118.00	3.84	8.47
5/B120GL	5	B	3048	120.00	3.91	8.62
5/B124GL	5	B	3150	124.00	4.04	8.90
5/B128GL	5	B	3251	128.00	4.17	9.19
5/B130GL	5	B	3302	130.00	4.23	9.34
5/B132GL	5	B	3353	132.00	4.30	9.48
5/B133GL	5	B	3378	133.00	4.33	9.55
5/B136GL	5	B	3454	136.00	4.43	9.77
5/B138GL	5	B	3505	138.00	4.49	9.91




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/B139GL	5	B	3531	139.00	4.53	9.98
5/B140GL	5	B	3556	140.00	4.56	10.05
5/B141GL	5	B	3581	141.00	4.59	10.12
5/B144GL	5	B	3658	144.00	4.69	10.34
5/B146GL	5	B	3708	146.00	4.76	10.48
5/B148GL	5	B	3759	148.00	4.82	10.63
5/B150GL	5	B	3810	150.00	4.89	10.77
5/B154GL	5	B	3912	154.00	5.02	11.06
5/B158GL	5	B	4013	158.00	5.15	11.35
5/B160GL	5	B	4064	160.00	5.21	11.49
5/B162GL	5	B	4115	162.00	5.28	11.63
5/B167GL	5	B	4242	167.00	5.44	11.99
5/B168GL	5	B	4267	168.00	5.47	12.06
5/B173GL	5	B	4394	173.00	5.63	12.42
5/B177GL	5	B	4496	177.00	5.77	12.71
5/B180GL	5	B	4572	180.00	5.86	12.93
5/B185GL	5	B	4699	185.00	6.03	13.28
5/B187GL	5	B	4750	187.00	6.09	13.43
5/B190GL	5	B	4826	190.00	6.19	13.64
5/B195GL	5	B	4953	195.00	6.35	14.00
5/B197GL	5	B	5004	197.00	6.42	14.15
5/B208GL	5	B	5283	208.00	6.77	14.94
5/B210GL	5	B	5334	210.00	6.84	15.08
5/B218GL	5	B	5537	218.00	7.10	15.65
5/B220GL	5	B	5588	220.00	7.17	15.80
5/B225GL	5	B	5715	225.00	7.33	16.16
5/B240GL	5	B	6096	240.00	7.82	17.23
5/B255GL	5	B	6477	255.00	8.31	18.31
5/B270GL	5	B	6858	270.00	8.79	19.39
5/B300GL	5	B	7620	300.00	9.77	21.54
5/B315GL	5	B	8001	315.00	10.26	22.62
16/B56GL	16	B	1422	56.00	5.84	12.87



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
16/B57GL	16	B	1448	57.00	5.94	13.10
16/B58GL	16	B	1473	58.00	6.05	13.33
16/B59GL	16	B	1499	59.00	6.15	13.56
16/B60GL	16	B	1524	60.00	6.25	13.79
16/B61GL	16	B	1549	61.00	6.36	14.02
16/B62GL	16	B	1575	62.00	6.46	14.25
16/B63GL	16	B	1600	63.00	6.57	14.48
16/B64GL	16	B	1626	64.00	6.67	14.71
16/B65GL	16	B	1651	65.00	6.77	14.94
16/B66GL	16	B	1676	66.00	6.88	15.17
16/B67GL	16	B	1702	67.00	6.98	15.40
16/B68GL	16	B	1727	68.00	7.09	15.63
16/B70GL	16	B	1778	70.00	7.30	16.08
16/B71GL	16	B	1803	71.00	7.40	16.31
16/B72GL	16	B	1829	72.00	7.50	16.54
16/B73GL	16	B	1854	73.00	7.61	16.77
16/B74GL	16	B	1880	74.00	7.71	17.00
16/B75GL	16	B	1905	75.00	7.82	17.23
16/B77GL	16	B	1956	77.00	8.03	17.69
16/B78GL	16	B	1981	78.00	8.13	17.92
16/B79GL	16	B	2007	79.00	8.23	18.15
16/B80GL	16	B	2032	80.00	8.34	18.38
16/B81GL	16	B	2057	81.00	8.44	18.61
16/B82GL	16	B	2083	82.00	8.55	18.84
16/B83GL	16	B	2108	83.00	8.65	19.07
16/B84GL	16	B	2134	84.00	8.76	19.30
16/B85GL	16	B	2159	85.00	8.86	19.53
24/B86GL	24	B	2184	86.00	13.45	29.64
24/B87GL	24	B	2210	87.00	13.60	29.99
24/B88GL	24	B	2235	88.00	13.76	30.33
24/B90GL	24	B	2286	90.00	14.07	31.02
24/B91GL	24	B	2311	91.00	14.23	31.37



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
24/B92GL	24	B	2337	92.00	14.38	31.71
24/B93GL	24	B	2362	93.00	14.54	32.05
24/B94.5GL	24	B	2400	94.50	14.77	32.57
24/B95GL	24	B	2413	95.00	14.85	32.74
24/B96GL	24	B	2438	96.00	15.01	33.09
24/B97GL	24	B	2464	97.00	15.17	33.43
24/B98GL	24	B	2489	98.00	15.32	33.78
24/B99GL	24	B	2515	99.00	15.48	34.12
24/B100GL	24	B	2540	100.00	15.63	34.47
24/B102GL	24	B	2591	102.00	15.95	35.16
24/B103GL	24	B	2616	103.00	16.10	35.50
24/B104GL	24	B	2642	104.00	16.26	35.85
24/B105GL	24	B	2667	105.00	16.42	36.19
24/B106GL	24	B	2692	106.00	16.57	36.54
24/B108GL	24	B	2743	108.00	16.89	37.23
24/B109GL	24	B	2769	109.00	17.04	37.57
24/B110GL	24	B	2794	110.00	17.20	37.91
24/B112GL	24	B	2845	112.00	17.51	38.60
24/B113GL	24	B	2870	113.00	17.67	38.95
24/B114GL	24	B	2896	114.00	17.82	39.29
24/B115GL	24	B	2921	115.00	17.98	39.64
24/B116GL	24	B	2946	116.00	18.14	39.98
24/B118GL	24	B	2997	118.00	18.45	40.67
24/B120GL	24	B	3048	120.00	18.76	41.36
24/B124GL	24	B	3150	124.00	19.39	42.74
24/B128GL	24	B	3251	128.00	20.01	44.12
24/B130GL	24	B	3302	130.00	20.32	44.81
24/B132GL	24	B	3353	132.00	20.64	45.50
24/B133GL	24	B	3378	133.00	20.79	45.84
24/B136GL	24	B	3454	136.00	21.26	46.88
24/B138GL	24	B	3505	138.00	21.58	47.57
24/B139GL	24	B	3531	139.00	21.73	47.91



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
24/B140GL	24	B	3556	140.00	21.89	48.25
24/B141GL	24	B	3581	141.00	22.04	48.60
24/B144GL	24	B	3658	144.00	22.51	49.63
24/B146GL	24	B	3708	146.00	22.83	50.32
24/B148GL	24	B	3759	148.00	23.14	51.01
24/B150GL	24	B	3810	150.00	23.45	51.70
24/B154GL	24	B	3912	154.00	24.08	53.08
24/B158GL	24	B	4013	158.00	24.70	54.46
24/B160GL	24	B	4064	160.00	25.01	55.15
24/B162GL	24	B	4115	162.00	25.33	55.84
24/B167GL	24	B	4242	167.00	26.11	57.56
24/B168GL	24	B	4267	168.00	26.27	57.91
24/B173GL	24	B	4394	173.00	27.05	59.63
24/B177GL	24	B	4496	177.00	27.67	61.01
24/B180GL	24	B	4572	180.00	28.14	62.04
24/B185GL	24	B	4699	185.00	28.92	63.77
24/B187GL	24	B	4750	187.00	29.24	64.45
24/B190GL	24	B	4826	190.00	29.71	65.49
24/B195GL	24	B	4953	195.00	30.49	67.21
24/B197GL	24	B	5004	197.00	30.80	67.90
24/B208GL	24	B	5283	208.00	32.52	71.69
24/B210GL	24	B	5334	210.00	32.83	72.38
24/B218GL	24	B	5537	218.00	34.08	75.14
24/B220GL	24	B	5588	220.00	34.40	75.83
24/B225GL	24	B	5715	225.00	35.18	77.55
24/B240GL	24	B	6096	240.00	37.52	82.72
24/B255GL	24	B	6477	255.00	39.87	87.89
24/B270GL	24	B	6858	270.00	42.21	93.06
24/B300GL	24	B	7620	300.00	46.90	103.40
24/B315GL	24	B	8001	315.00	49.25	108.57
2/C60GL	2	C	1524	60.00	1.37	3.03
2/C68GL	2	C	1727	68.00	1.56	3.43



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/C72GL	2	C	1829	72.00	1.65	3.64
2/C75GL	2	C	1905	75.00	1.72	3.79
2/C78GL	2	C	1981	78.00	1.79	3.94
2/C80GL	2	C	2032	80.00	1.83	4.04
2/C81GL	2	C	2057	81.00	1.86	4.09
2/C85GL	2	C	2159	85.00	1.95	4.29
2/C87GL	2	C	2210	87.00	1.99	4.39
2/C90GL	2	C	2286	90.00	2.06	4.54
2/C96GL	2	C	2438	96.00	2.20	4.85
2/C98GL	2	C	2489	98.00	2.24	4.95
2/C99GL	2	C	2515	99.00	2.27	5.00
2/C100GL	2	C	2540	100.00	2.29	5.05
2/C105GL	2	C	2667	105.00	2.40	5.30
2/C108GL	2	C	2743	108.00	2.47	5.45
2/C109GL	2	C	2769	109.00	2.50	5.50
2/C112GL	2	C	2845	112.00	2.57	5.65
2/C120GL	2	C	3048	120.00	2.75	6.06
2/C124GL	2	C	3150	124.00	2.84	6.26
2/C126GL	2	C	3200	126.00	2.89	6.36
2/C128GL	2	C	3251	128.00	2.93	6.46
2/C136GL	2	C	3454	136.00	3.11	6.87
2/C140GL	2	C	3556	140.00	3.21	7.07
2/C144GL	2	C	3658	144.00	3.30	7.27
2/C146GL	2	C	3708	146.00	3.34	7.37
2/C151GL	2	C	3835	151.00	3.46	7.62
2/C158GL	2	C	4013	158.00	3.62	7.98
2/C162GL	2	C	4115	162.00	3.71	8.18
2/C167GL	2	C	4242	167.00	3.82	8.43
2/C173GL	2	C	4394	173.00	3.96	8.73
2/C177GL	2	C	4496	177.00	4.05	8.94
2/C180GL	2	C	4572	180.00	4.12	9.09
2/C185GL	2	C	4699	185.00	4.24	9.34



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/C187GL	2	C	4750	187.00	4.28	9.44
2/C190GL	2	C	4826	190.00	4.35	9.59
2/C195GL	2	C	4953	195.00	4.47	9.85
2/C197GL	2	C	5004	197.00	4.51	9.95
2/C204GL	2	C	5182	204.00	4.67	10.30
2/C208GL	2	C	5283	208.00	4.76	10.50
2/C210GL	2	C	5334	210.00	4.81	10.60
2/C220GL	2	C	5588	220.00	5.04	11.11
2/C225GL	2	C	5715	225.00	5.15	11.36
2/C236GL	2	C	5994	236.00	5.40	11.92
2/C240GL	2	C	6096	240.00	5.50	12.12
2/C248GL	2	C	6299	248.00	5.68	12.52
2/C255GL	2	C	6477	255.00	5.84	12.87
2/C270GL	2	C	6858	270.00	6.18	13.63
2/C285GL	2	C	7239	285.00	6.53	14.39
2/C300GL	2	C	7620	300.00	6.87	15.15
2/C315GL	2	C	8001	315.00	7.21	15.90
2/C330GL	2	C	8382	330.00	7.56	16.66
2/C345GL	2	C	8763	345.00	7.90	17.42
2/C360GL	2	C	9144	360.00	8.24	18.18
2/C390GL	2	C	9906	390.00	8.93	19.69
2/C420GL	2	C	10668	420.00	9.62	21.21
3/C60GL	3	C	1524	60.00	2.06	4.54
3/C68GL	3	C	1727	68.00	2.34	5.15
3/C72GL	3	C	1829	72.00	2.47	5.45
3/C75GL	3	C	1905	75.00	2.58	5.68
3/C78GL	3	C	1981	78.00	2.68	5.91
3/C80GL	3	C	2032	80.00	2.75	6.06
3/C81GL	3	C	2057	81.00	2.78	6.13
3/C85GL	3	C	2159	85.00	2.92	6.44
3/C87GL	3	C	2210	87.00	2.99	6.59
3/C90GL	3	C	2286	90.00	3.09	6.82




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/C96GL	3	C	2438	96.00	3.30	7.27
3/C98GL	3	C	2489	98.00	3.37	7.42
3/C99GL	3	C	2515	99.00	3.40	7.50
3/C100GL	3	C	2540	100.00	3.44	7.57
3/C105GL	3	C	2667	105.00	3.61	7.95
3/C108GL	3	C	2743	108.00	3.71	8.18
3/C109GL	3	C	2769	109.00	3.74	8.26
3/C112GL	3	C	2845	112.00	3.85	8.48
3/C120GL	3	C	3048	120.00	4.12	9.09
3/C124GL	3	C	3150	124.00	4.26	9.39
3/C126GL	3	C	3200	126.00	4.33	9.54
3/C128GL	3	C	3251	128.00	4.40	9.69
3/C136GL	3	C	3454	136.00	4.67	10.30
3/C140GL	3	C	3556	140.00	4.81	10.60
3/C144GL	3	C	3658	144.00	4.95	10.91
3/C146GL	3	C	3708	146.00	5.02	11.06
3/C151GL	3	C	3835	151.00	5.19	11.44
3/C158GL	3	C	4013	158.00	5.43	11.97
3/C162GL	3	C	4115	162.00	5.57	12.27
3/C167GL	3	C	4242	167.00	5.74	12.65
3/C173GL	3	C	4394	173.00	5.94	13.10
3/C177GL	3	C	4496	177.00	6.08	13.41
3/C180GL	3	C	4572	180.00	6.18	13.63
3/C185GL	3	C	4699	185.00	6.36	14.01
3/C187GL	3	C	4750	187.00	6.42	14.16
3/C190GL	3	C	4826	190.00	6.53	14.39
3/C195GL	3	C	4953	195.00	6.70	14.77
3/C197GL	3	C	5004	197.00	6.77	14.92
3/C204GL	3	C	5182	204.00	7.01	15.45
3/C208GL	3	C	5283	208.00	7.15	15.75
3/C210GL	3	C	5334	210.00	7.21	15.90
3/C220GL	3	C	5588	220.00	7.56	16.66




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/C225GL	3	C	5715	225.00	7.73	17.04
3/C236GL	3	C	5994	236.00	8.11	17.87
3/C240GL	3	C	6096	240.00	8.24	18.18
3/C248GL	3	C	6299	248.00	8.52	18.78
3/C255GL	3	C	6477	255.00	8.76	19.31
3/C270GL	3	C	6858	270.00	9.28	20.45
3/C285GL	3	C	7239	285.00	9.79	21.58
3/C300GL	3	C	7620	300.00	10.31	22.72
3/C315GL	3	C	8001	315.00	10.82	23.86
3/C330GL	3	C	8382	330.00	11.34	24.99
3/C345GL	3	C	8763	345.00	11.85	26.13
3/C360GL	3	C	9144	360.00	12.37	27.26
3/C390GL	3	C	9906	390.00	13.40	29.54
3/C420GL	3	C	10668	420.00	14.43	31.81
4/C60GL	4	C	1524	60.00	2.75	6.06
4/C68GL	4	C	1727	68.00	3.11	6.87
4/C72GL	4	C	1829	72.00	3.30	7.27
4/C75GL	4	C	1905	75.00	3.44	7.57
4/C78GL	4	C	1981	78.00	3.57	7.88
4/C80GL	4	C	2032	80.00	3.66	8.08
4/C81GL	4	C	2057	81.00	3.71	8.18
4/C85GL	4	C	2159	85.00	3.89	8.58
4/C87GL	4	C	2210	87.00	3.98	8.79
4/C90GL	4	C	2286	90.00	4.12	9.09
4/C96GL	4	C	2438	96.00	4.40	9.69
4/C98GL	4	C	2489	98.00	4.49	9.90
4/C99GL	4	C	2515	99.00	4.53	10.00
4/C100GL	4	C	2540	100.00	4.58	10.10
4/C105GL	4	C	2667	105.00	4.81	10.60
4/C108GL	4	C	2743	108.00	4.95	10.91
4/C109GL	4	C	2769	109.00	4.99	11.01
4/C112GL	4	C	2845	112.00	5.13	11.31



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/C120GL	4	C	3048	120.00	5.50	12.12
4/C124GL	4	C	3150	124.00	5.68	12.52
4/C126GL	4	C	3200	126.00	5.77	12.72
4/C128GL	4	C	3251	128.00	5.86	12.93
4/C136GL	4	C	3454	136.00	6.23	13.73
4/C140GL	4	C	3556	140.00	6.41	14.14
4/C144GL	4	C	3658	144.00	6.60	14.54
4/C146GL	4	C	3708	146.00	6.69	14.74
4/C151GL	4	C	3835	151.00	6.92	15.25
4/C158GL	4	C	4013	158.00	7.24	15.95
4/C162GL	4	C	4115	162.00	7.42	16.36
4/C167GL	4	C	4242	167.00	7.65	16.86
4/C173GL	4	C	4394	173.00	7.92	17.47
4/C177GL	4	C	4496	177.00	8.11	17.87
4/C180GL	4	C	4572	180.00	8.24	18.18
4/C185GL	4	C	4699	185.00	8.47	18.68
4/C187GL	4	C	4750	187.00	8.57	18.88
4/C190GL	4	C	4826	190.00	8.70	19.19
4/C195GL	4	C	4953	195.00	8.93	19.69
4/C197GL	4	C	5004	197.00	9.02	19.89
4/C204GL	4	C	5182	204.00	9.34	20.60
4/C208GL	4	C	5283	208.00	9.53	21.00
4/C210GL	4	C	5334	210.00	9.62	21.21
4/C220GL	4	C	5588	220.00	10.08	22.22
4/C225GL	4	C	5715	225.00	10.31	22.72
4/C236GL	4	C	5994	236.00	10.81	23.83
4/C240GL	4	C	6096	240.00	10.99	24.24
4/C248GL	4	C	6299	248.00	11.36	25.04
4/C255GL	4	C	6477	255.00	11.68	25.75
4/C270GL	4	C	6858	270.00	12.37	27.26
4/C285GL	4	C	7239	285.00	13.05	28.78
4/C300GL	4	C	7620	300.00	13.74	30.29



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/C315GL	4	C	8001	315.00	14.43	31.81
4/C330GL	4	C	8382	330.00	15.12	33.32
4/C345GL	4	C	8763	345.00	15.80	34.84
4/C360GL	4	C	9144	360.00	16.49	36.35
4/C390GL	4	C	9906	390.00	17.86	39.38
4/C420GL	4	C	10668	420.00	19.24	42.41
5/C60GL	5	C	1524	60.00	3.44	7.57
5/C68GL	5	C	1727	68.00	3.89	8.58
5/C72GL	5	C	1829	72.00	4.12	9.09
5/C75GL	5	C	1905	75.00	4.29	9.47
5/C78GL	5	C	1981	78.00	4.47	9.85
5/C80GL	5	C	2032	80.00	4.58	10.10
5/C81GL	5	C	2057	81.00	4.64	10.22
5/C85GL	5	C	2159	85.00	4.87	10.73
5/C87GL	5	C	2210	87.00	4.98	10.98
5/C90GL	5	C	2286	90.00	5.15	11.36
5/C96GL	5	C	2438	96.00	5.50	12.12
5/C98GL	5	C	2489	98.00	5.61	12.37
5/C99GL	5	C	2515	99.00	5.67	12.50
5/C100GL	5	C	2540	100.00	5.73	12.62
5/C105GL	5	C	2667	105.00	6.01	13.25
5/C108GL	5	C	2743	108.00	6.18	13.63
5/C109GL	5	C	2769	109.00	6.24	13.76
5/C112GL	5	C	2845	112.00	6.41	14.14
5/C120GL	5	C	3048	120.00	6.87	15.15
5/C124GL	5	C	3150	124.00	7.10	15.65
5/C126GL	5	C	3200	126.00	7.21	15.90
5/C128GL	5	C	3251	128.00	7.33	16.16
5/C136GL	5	C	3454	136.00	7.79	17.17
5/C140GL	5	C	3556	140.00	8.02	17.67
5/C144GL	5	C	3658	144.00	8.24	18.18
5/C146GL	5	C	3708	146.00	8.36	18.43



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/C151GL	5	C	3835	151.00	8.65	19.06
5/C158GL	5	C	4013	158.00	9.05	19.94
5/C162GL	5	C	4115	162.00	9.28	20.45
5/C167GL	5	C	4242	167.00	9.56	21.08
5/C173GL	5	C	4394	173.00	9.91	21.84
5/C177GL	5	C	4496	177.00	10.13	22.34
5/C180GL	5	C	4572	180.00	10.31	22.72
5/C185GL	5	C	4699	185.00	10.59	23.35
5/C187GL	5	C	4750	187.00	10.71	23.60
5/C190GL	5	C	4826	190.00	10.88	23.98
5/C195GL	5	C	4953	195.00	11.16	24.61
5/C197GL	5	C	5004	197.00	11.28	24.87
5/C204GL	5	C	5182	204.00	11.68	25.75
5/C208GL	5	C	5283	208.00	11.91	26.25
5/C210GL	5	C	5334	210.00	12.02	26.51
5/C220GL	5	C	5588	220.00	12.60	27.77
5/C225GL	5	C	5715	225.00	12.88	28.40
5/C236GL	5	C	5994	236.00	13.51	29.79
5/C240GL	5	C	6096	240.00	13.74	30.29
5/C248GL	5	C	6299	248.00	14.20	31.30
5/C255GL	5	C	6477	255.00	14.60	32.19
5/C270GL	5	C	6858	270.00	15.46	34.08
5/C285GL	5	C	7239	285.00	16.32	35.97
5/C300GL	5	C	7620	300.00	17.18	37.87
5/C315GL	5	C	8001	315.00	18.04	39.76
5/C330GL	5	C	8382	330.00	18.89	41.65
5/C345GL	5	C	8763	345.00	19.75	43.55
5/C360GL	5	C	9144	360.00	20.61	45.44
5/C390GL	5	C	9906	390.00	22.33	49.23
5/C420GL	5	C	10668	420.00	24.05	53.01
12/C60GL	12	C	1524	60.00	8.24	18.18
12/C68GL	12	C	1727	68.00	9.34	20.60



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
12/C72GL	12	C	1829	72.00	9.89	21.81
12/C75GL	12	C	1905	75.00	10.31	22.72
12/C78GL	12	C	1981	78.00	10.72	23.63
12/C80GL	12	C	2032	80.00	10.99	24.24
12/C81GL	12	C	2057	81.00	11.13	24.54
12/C85GL	12	C	2159	85.00	11.68	25.75
18/C87GL	18	C	2210	87.00	17.93	39.53
18/C90GL	18	C	2286	90.00	18.55	40.90
18/C96GL	18	C	2438	96.00	19.79	43.62
18/C98GL	18	C	2489	98.00	20.20	44.53
18/C99GL	18	C	2515	99.00	20.41	44.99
18/C100GL	18	C	2540	100.00	20.61	45.44
18/C105GL	18	C	2667	105.00	21.64	47.71
18/C108GL	18	C	2743	108.00	22.26	49.08
18/C109GL	18	C	2769	109.00	22.47	49.53
18/C112GL	18	C	2845	112.00	23.09	50.89
18/C120GL	18	C	3048	120.00	24.73	54.53
18/C124GL	18	C	3150	124.00	25.56	56.35
18/C126GL	18	C	3200	126.00	25.97	57.26
18/C128GL	18	C	3251	128.00	26.38	58.16
18/C136GL	18	C	3454	136.00	28.03	61.80
18/C140GL	18	C	3556	140.00	28.86	63.62
18/C144GL	18	C	3658	144.00	29.68	65.43
18/C146GL	18	C	3708	146.00	30.09	66.34
18/C151GL	18	C	3835	151.00	31.12	68.62
18/C158GL	18	C	4013	158.00	32.57	71.80
18/C162GL	18	C	4115	162.00	33.39	73.61
18/C167GL	18	C	4242	167.00	34.42	75.89
18/C173GL	18	C	4394	173.00	35.66	78.61
18/C177GL	18	C	4496	177.00	36.48	80.43
18/C180GL	18	C	4572	180.00	37.10	81.79
18/C185GL	18	C	4699	185.00	38.13	84.07



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
18/C187GL	18	C	4750	187.00	38.54	84.97
18/C190GL	18	C	4826	190.00	39.16	86.34
18/C195GL	18	C	4953	195.00	40.19	88.61
18/C197GL	18	C	5004	197.00	40.60	89.52
18/C204GL	18	C	5182	204.00	42.05	92.70
18/C208GL	18	C	5283	208.00	42.87	94.52
18/C210GL	18	C	5334	210.00	43.28	95.43
18/C220GL	18	C	5588	220.00	45.35	99.97
18/C225GL	18	C	5715	225.00	46.38	102.24
18/C236GL	18	C	5994	236.00	48.64	107.24
18/C240GL	18	C	6096	240.00	49.47	109.06
18/C248GL	18	C	6299	248.00	51.12	112.69
18/C255GL	18	C	6477	255.00	52.56	115.87
18/C270GL	18	C	6858	270.00	55.65	122.69
18/C285GL	18	C	7239	285.00	58.74	129.51
18/C300GL	18	C	7620	300.00	61.84	136.32
18/C315GL	18	C	8001	315.00	64.93	143.14
18/C330GL	18	C	8382	330.00	68.02	149.96
18/C345GL	18	C	8763	345.00	71.11	156.77
18/C360GL	18	C	9144	360.00	74.20	163.59
18/C390GL	18	C	9906	390.00	80.39	177.22
18/C420GL	18	C	10668	420.00	86.57	190.85
2/D110GL	2	D	2794	110.00	4.47	9.85
2/D120GL	2	D	3048	120.00	4.87	10.75
2/D128GL	2	D	3251	128.00	5.20	11.46
2/D144GL	2	D	3658	144.00	5.85	12.89
2/D158GL	2	D	4013	158.00	6.42	14.15
2/D162GL	2	D	4115	162.00	6.58	14.51
2/D173GL	2	D	4394	173.00	7.03	15.49
2/D180GL	2	D	4572	180.00	7.31	16.12
2/D195GL	2	D	4953	195.00	7.92	17.46
2/D210GL	2	D	5334	210.00	8.53	18.80



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/D225GL	2	D	5715	225.00	9.14	20.15
2/D240GL	2	D	6096	240.00	9.75	21.49
2/D255GL	2	D	6477	255.00	10.36	22.83
2/D270GL	2	D	6858	270.00	10.97	24.18
2/D285GL	2	D	7239	285.00	11.58	25.52
2/D300GL	2	D	7620	300.00	12.19	26.86
2/D315GL	2	D	8001	315.00	12.79	28.21
2/D330GL	2	D	8382	330.00	13.40	29.55
2/D345GL	2	D	8763	345.00	14.01	30.89
2/D360GL	2	D	9144	360.00	14.62	32.24
2/D390GL	2	D	9906	390.00	15.84	34.92
2/D420GL	2	D	10668	420.00	17.06	37.61
2/D450GL	2	D	11430	450.00	18.28	40.30
2/D480GL	2	D	12192	480.00	19.50	42.98
2/D540GL	2	D	13716	540.00	21.93	48.35
2/D600GL	2	D	15240	600.00	24.37	53.73
2/D660GL	2	D	16764	660.00	26.81	59.10
2/D700GL	2	D	17780	700.00	28.43	62.68
3/D110GL	3	D	2794	110.00	6.70	14.77
3/D120GL	3	D	3048	120.00	7.31	16.12
3/D128GL	3	D	3251	128.00	7.80	17.19
3/D144GL	3	D	3658	144.00	8.77	19.34
3/D158GL	3	D	4013	158.00	9.63	21.22
3/D162GL	3	D	4115	162.00	9.87	21.76
3/D173GL	3	D	4394	173.00	10.54	23.24
3/D180GL	3	D	4572	180.00	10.97	24.18
3/D195GL	3	D	4953	195.00	11.88	26.19
3/D210GL	3	D	5334	210.00	12.79	28.21
3/D225GL	3	D	5715	225.00	13.71	30.22
3/D240GL	3	D	6096	240.00	14.62	32.24
3/D255GL	3	D	6477	255.00	15.54	34.25
3/D270GL	3	D	6858	270.00	16.45	36.27



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/D285GL	3	D	7239	285.00	17.36	38.28
3/D300GL	3	D	7620	300.00	18.28	40.30
3/D315GL	3	D	8001	315.00	19.19	42.31
3/D330GL	3	D	8382	330.00	20.11	44.32
3/D345GL	3	D	8763	345.00	21.02	46.34
3/D360GL	3	D	9144	360.00	21.93	48.35
3/D390GL	3	D	9906	390.00	23.76	52.38
3/D420GL	3	D	10668	420.00	25.59	56.41
3/D450GL	3	D	11430	450.00	27.42	60.44
3/D480GL	3	D	12192	480.00	29.24	64.47
3/D540GL	3	D	13716	540.00	32.90	72.53
3/D600GL	3	D	15240	600.00	36.56	80.59
3/D660GL	3	D	16764	660.00	40.21	88.65
3/D700GL	3	D	17780	700.00	42.65	94.02
4/D110GL	4	D	2794	110.00	8.94	19.70
4/D120GL	4	D	3048	120.00	9.75	21.49
4/D128GL	4	D	3251	128.00	10.40	22.92
4/D144GL	4	D	3658	144.00	11.70	25.79
4/D158GL	4	D	4013	158.00	12.83	28.30
4/D162GL	4	D	4115	162.00	13.16	29.01
4/D173GL	4	D	4394	173.00	14.05	30.98
4/D180GL	4	D	4572	180.00	14.62	32.24
4/D195GL	4	D	4953	195.00	15.84	34.92
4/D210GL	4	D	5334	210.00	17.06	37.61
4/D225GL	4	D	5715	225.00	18.28	40.30
4/D240GL	4	D	6096	240.00	19.50	42.98
4/D255GL	4	D	6477	255.00	20.71	45.67
4/D270GL	4	D	6858	270.00	21.93	48.35
4/D285GL	4	D	7239	285.00	23.15	51.04
4/D300GL	4	D	7620	300.00	24.37	53.73
4/D315GL	4	D	8001	315.00	25.59	56.41
4/D330GL	4	D	8382	330.00	26.81	59.10



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/D345GL	4	D	8763	345.00	28.03	61.79
4/D360GL	4	D	9144	360.00	29.24	64.47
4/D390GL	4	D	9906	390.00	31.68	69.84
4/D420GL	4	D	10668	420.00	34.12	75.22
4/D450GL	4	D	11430	450.00	36.56	80.59
4/D480GL	4	D	12192	480.00	38.99	85.96
4/D540GL	4	D	13716	540.00	43.87	96.71
4/D600GL	4	D	15240	600.00	48.74	107.45
4/D660GL	4	D	16764	660.00	53.61	118.20
4/D700GL	4	D	17780	700.00	56.86	125.36
5/D110GL	5	D	2794	110.00	11.17	24.62
5/D120GL	5	D	3048	120.00	12.19	26.86
5/D128GL	5	D	3251	128.00	13.00	28.65
5/D144GL	5	D	3658	144.00	14.62	32.24
5/D158GL	5	D	4013	158.00	16.04	35.37
5/D162GL	5	D	4115	162.00	16.45	36.27
5/D173GL	5	D	4394	173.00	17.57	38.73
5/D180GL	5	D	4572	180.00	18.28	40.30
5/D195GL	5	D	4953	195.00	19.80	43.65
5/D210GL	5	D	5334	210.00	21.32	47.01
5/D225GL	5	D	5715	225.00	22.85	50.37
5/D240GL	5	D	6096	240.00	24.37	53.73
5/D255GL	5	D	6477	255.00	25.89	57.08
5/D270GL	5	D	6858	270.00	27.42	60.44
5/D285GL	5	D	7239	285.00	28.94	63.80
5/D300GL	5	D	7620	300.00	30.46	67.16
5/D315GL	5	D	8001	315.00	31.99	70.52
5/D330GL	5	D	8382	330.00	33.51	73.87
5/D345GL	5	D	8763	345.00	35.03	77.23
5/D360GL	5	D	9144	360.00	36.56	80.59
5/D390GL	5	D	9906	390.00	39.60	87.31
5/D420GL	5	D	10668	420.00	42.65	94.02



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available


DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/D450GL	5	D	11430	450.00	45.69	100.74
5/D480GL	5	D	12192	480.00	48.74	107.45
5/D540GL	5	D	13716	540.00	54.83	120.89
5/D600GL	5	D	15240	600.00	60.93	134.32
5/D660GL	5	D	16764	660.00	67.02	147.75
5/D700GL	5	D	17780	700.00	71.08	156.70
12/D110GL	12	D	2794	110.00	26.81	59.10
12/D120GL	12	D	3048	120.00	29.24	64.47
12/D128GL	12	D	3251	128.00	31.19	68.77
12/D144GL	12	D	3658	144.00	35.09	77.37
12/D660GL	12	D	16764	660.00	160.84	354.60
12/D700GL	12	D	17780	700.00	170.59	376.09
20/D158GL	20	D	4013	158.00	64.17	141.48
20/D162GL	20	D	4115	162.00	65.80	145.06
20/D173GL	20	D	4394	173.00	70.27	154.91
20/D180GL	20	D	4572	180.00	73.11	161.18
20/D195GL	20	D	4953	195.00	79.20	174.61
20/D210GL	20	D	5334	210.00	85.30	188.04
20/D225GL	20	D	5715	225.00	91.39	201.48
20/D240GL	20	D	6096	240.00	97.48	214.91
20/D255GL	20	D	6477	255.00	103.57	228.34
20/D270GL	20	D	6858	270.00	109.67	241.77
20/D285GL	20	D	7239	285.00	115.76	255.20
20/D300GL	20	D	7620	300.00	121.85	268.63
20/D315GL	20	D	8001	315.00	127.94	282.07
20/D330GL	20	D	8382	330.00	134.04	295.50
20/D345GL	20	D	8763	345.00	140.13	308.93
20/D360GL	20	D	9144	360.00	146.22	322.36
20/D390GL	20	D	9906	390.00	158.41	349.22
20/D420GL	20	D	10668	420.00	170.59	376.09
20/D450GL	20	D	11430	450.00	182.78	402.95
20/D480GL	20	D	12192	480.00	194.96	429.81
20/D540GL	20	D	13716	540.00	219.33	483.54
20/D600GL	20	D	15240	600.00	243.70	537.27

GOLD LABEL Banded Wrapped Narrow - Product Description



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

V-Belt

Part Number Description: **2/3V800GL**

2/: Number of ribs

3V: Profile

800: External Length (tenths of an inch)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, Rubber Impregnated

- Abrasion, wear and oil resistance
- Prevents vibrations and belt turn-over

Fabric Cover: PET/Cotton, Rubber Impregnated

- Abrasion, wear and oil resistance
- Static conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber Blend

- High resistance to bending stress
- Superior oil and heat resistance
- Temperature range: -31°F (-35°C) to 160°F (70 °C)

Up to 3 times the power transmission capacity compared to classical V profiles (A, B, C, D)

Markets and Applications:


Designed for high horsepower and shock load applications, these industrial banded belts are primarily employed on applications where multiple belts have the tendency to vibrate, turn over or come off pulleys when subjected to fluctuating load tensions and high horsepower.

The Dayco GOLD LABEL industrial banded belt is available in both wrapped molded construction and raw edge versions and provides the same oil and heat resistant characteristics as the Dayco GOLD LABEL single belts with the addition of a fabric rubber top band for multiple belt stability.




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/3V600GL	2	3V	1524	60.00	0.31	0.69
2/3V630GL	2	3V	1600	63.00	0.33	0.73
2/3V670GL	2	3V	1702	67.00	0.35	0.77
2/3V710GL	2	3V	1803	71.00	0.37	0.82
2/3V750GL	2	3V	1905	75.00	0.39	0.87
2/3V800GL	2	3V	2032	80.00	0.42	0.92
2/3V850GL	2	3V	2159	85.00	0.45	0.98
2/3V900GL	2	3V	2286	90.00	0.47	1.04
2/3V950GL	2	3V	2413	95.00	0.50	1.10
2/3V1000GL	2	3V	2540	100.00	0.52	1.15
2/3V1060GL	2	3V	2692	106.00	0.56	1.22
2/3V1120GL	2	3V	2845	112.00	0.59	1.29
2/3V1180GL	2	3V	2997	118.00	0.62	1.36
2/3V1250GL	2	3V	3175	125.00	0.65	1.44
2/3V1320GL	2	3V	3353	132.00	0.69	1.52
2/3V1400GL	2	3V	3556	140.00	0.73	1.62
3/3V600GL	3	3V	1524	60.00	0.47	1.04
3/3V630GL	3	3V	1600	63.00	0.49	1.09
3/3V670GL	3	3V	1702	67.00	0.53	1.16
3/3V710GL	3	3V	1803	71.00	0.56	1.23
3/3V750GL	3	3V	1905	75.00	0.59	1.30
3/3V800GL	3	3V	2032	80.00	0.63	1.39
3/3V850GL	3	3V	2159	85.00	0.67	1.47
3/3V900GL	3	3V	2286	90.00	0.71	1.56
3/3V950GL	3	3V	2413	95.00	0.75	1.65
3/3V1000GL	3	3V	2540	100.00	0.79	1.73
3/3V1060GL	3	3V	2692	106.00	0.83	1.84
3/3V1120GL	3	3V	2845	112.00	0.88	1.94
3/3V1180GL	3	3V	2997	118.00	0.93	2.04
3/3V1250GL	3	3V	3175	125.00	0.98	2.17
3/3V1320GL	3	3V	3353	132.00	1.04	2.29
3/3V1400GL	3	3V	3556	140.00	1.10	2.42
4/3V600GL	4	3V	1524	60.00	0.63	1.39
4/3V630GL	4	3V	1600	63.00	0.66	1.45




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
4/3V670GL	4	3V	1702	67.00	0.70	1.55
4/3V710GL	4	3V	1803	71.00	0.74	1.64
4/3V750GL	4	3V	1905	75.00	0.79	1.73
4/3V800GL	4	3V	2032	80.00	0.84	1.85
4/3V850GL	4	3V	2159	85.00	0.89	1.96
4/3V900GL	4	3V	2286	90.00	0.94	2.08
4/3V950GL	4	3V	2413	95.00	1.00	2.19
4/3V1000GL	4	3V	2540	100.00	1.05	2.31
4/3V1060GL	4	3V	2692	106.00	1.11	2.45
4/3V1120GL	4	3V	2845	112.00	1.17	2.59
4/3V1180GL	4	3V	2997	118.00	1.24	2.73
4/3V1250GL	4	3V	3175	125.00	1.31	2.89
4/3V1320GL	4	3V	3353	132.00	1.38	3.05
4/3V1400GL	4	3V	3556	140.00	1.47	3.23
5/3V600GL	5	3V	1524	60.00	0.79	1.73
5/3V630GL	5	3V	1600	63.00	0.82	1.82
5/3V670GL	5	3V	1702	67.00	0.88	1.93
5/3V710GL	5	3V	1803	71.00	0.93	2.05
5/3V750GL	5	3V	1905	75.00	0.98	2.17
5/3V800GL	5	3V	2032	80.00	1.05	2.31
5/3V850GL	5	3V	2159	85.00	1.11	2.45
5/3V900GL	5	3V	2286	90.00	1.18	2.60
5/3V950GL	5	3V	2413	95.00	1.24	2.74
5/3V1000GL	5	3V	2540	100.00	1.31	2.89
5/3V1060GL	5	3V	2692	106.00	1.39	3.06
5/3V1120GL	5	3V	2845	112.00	1.47	3.23
5/3V1180GL	5	3V	2997	118.00	1.55	3.41
5/3V1250GL	5	3V	3175	125.00	1.64	3.61
5/3V1320GL	5	3V	3353	132.00	1.73	3.81
5/3V1400GL	5	3V	3556	140.00	1.83	4.04
29/3V600GL	29	3V	1524	60.00	4.56	10.05
29/3V630GL	29	3V	1600	63.00	4.78	10.55
29/3V670GL	29	3V	1702	67.00	5.09	11.22
29/3V710GL	29	3V	1803	71.00	5.39	11.89




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
29/3V750GL	29	3V	1905	75.00	5.70	12.56
29/3V800GL	29	3V	2032	80.00	6.08	13.40
29/3V850GL	29	3V	2159	85.00	6.46	14.23
29/3V900GL	29	3V	2286	90.00	6.84	15.07
29/3V950GL	29	3V	2413	95.00	7.22	15.91
29/3V1000GL	29	3V	2540	100.00	7.59	16.74
29/3V1060GL	29	3V	2692	106.00	8.05	17.75
29/3V1120GL	29	3V	2845	112.00	8.51	18.75
29/3V1180GL	29	3V	2997	118.00	8.96	19.76
29/3V1250GL	29	3V	3175	125.00	9.49	20.93
29/3V1320GL	29	3V	3353	132.00	10.03	22.10
29/3V1400GL	29	3V	3556	140.00	10.63	23.44
2/5V600GL	2	5V	1524	60.00	0.85	1.88
2/5V630GL	2	5V	1600	63.00	0.90	1.97
2/5V670GL	2	5V	1702	67.00	0.95	2.10
2/5V710GL	2	5V	1803	71.00	1.01	2.23
2/5V750GL	2	5V	1905	75.00	1.07	2.35
2/5V800GL	2	5V	2032	80.00	1.14	2.51
2/5V850GL	2	5V	2159	85.00	1.21	2.66
2/5V900GL	2	5V	2286	90.00	1.28	2.82
2/5V950GL	2	5V	2413	95.00	1.35	2.98
2/5V1000GL	2	5V	2540	100.00	1.42	3.13
2/5V1060GL	2	5V	2692	106.00	1.51	3.32
2/5V1120GL	2	5V	2845	112.00	1.59	3.51
2/5V1180GL	2	5V	2997	118.00	1.68	3.70
2/5V1200GL	2	5V	3048	120.00	1.71	3.76
2/5V1210GL	2	5V	3073	121.00	1.72	3.79
2/5V1250GL	2	5V	3175	125.00	1.78	3.92
2/5V1320GL	2	5V	3353	132.00	1.88	4.14
2/5V1400GL	2	5V	3556	140.00	1.99	4.39
2/5V1500GL	2	5V	3810	150.00	2.13	4.70
2/5V1600GL	2	5V	4064	160.00	2.27	5.01
2/5V1700GL	2	5V	4318	170.00	2.42	5.33
2/5V1800GL	2	5V	4572	180.00	2.56	5.64




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/5V1900GL	2	5V	4826	190.00	2.70	5.95
2/5V2000GL	2	5V	5080	200.00	2.84	6.27
2/5V2120GL	2	5V	5385	212.00	3.01	6.64
2/5V2240GL	2	5V	5690	224.00	3.18	7.02
2/5V2360GL	2	5V	5994	236.00	3.35	7.40
2/5V2500GL	2	5V	6350	250.00	3.55	7.83
2/5V2650GL	2	5V	6731	265.00	3.77	8.30
2/5V2800GL	2	5V	7112	280.00	3.98	8.78
2/5V3000GL	2	5V	7620	300.00	4.26	9.40
2/5V3150GL	2	5V	8001	315.00	4.48	9.87
2/5V3350GL	2	5V	8509	335.00	4.76	10.50
2/5V3550GL	2	5V	9017	355.00	5.05	11.13
3/5V600GL	3	5V	1524	60.00	1.28	2.82
3/5V630GL	3	5V	1600	63.00	1.34	2.96
3/5V670GL	3	5V	1702	67.00	1.43	3.15
3/5V710GL	3	5V	1803	71.00	1.51	3.34
3/5V750GL	3	5V	1905	75.00	1.60	3.53
3/5V800GL	3	5V	2032	80.00	1.71	3.76
3/5V850GL	3	5V	2159	85.00	1.81	4.00
3/5V900GL	3	5V	2286	90.00	1.92	4.23
3/5V950GL	3	5V	2413	95.00	2.03	4.47
3/5V1000GL	3	5V	2540	100.00	2.13	4.70
3/5V1060GL	3	5V	2692	106.00	2.26	4.98
3/5V1120GL	3	5V	2845	112.00	2.39	5.27
3/5V1180GL	3	5V	2997	118.00	2.52	5.55
3/5V1200GL	3	5V	3048	120.00	2.56	5.64
3/5V1210GL	3	5V	3073	121.00	2.58	5.69
3/5V1250GL	3	5V	3175	125.00	2.67	5.88
3/5V1320GL	3	5V	3353	132.00	2.81	6.21
3/5V1400GL	3	5V	3556	140.00	2.99	6.58
3/5V1500GL	3	5V	3810	150.00	3.20	7.05
3/5V1600GL	3	5V	4064	160.00	3.41	7.52
3/5V1700GL	3	5V	4318	170.00	3.62	7.99
3/5V1800GL	3	5V	4572	180.00	3.84	8.46




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
3/5V1900GL	3	5V	4826	190.00	4.05	8.93
3/5V2000GL	3	5V	5080	200.00	4.26	9.40
3/5V2120GL	3	5V	5385	212.00	4.52	9.97
3/5V2240GL	3	5V	5690	224.00	4.78	10.53
3/5V2360GL	3	5V	5994	236.00	5.03	11.09
3/5V2500GL	3	5V	6350	250.00	5.33	11.75
3/5V2650GL	3	5V	6731	265.00	5.65	12.46
3/5V2800GL	3	5V	7112	280.00	5.97	13.16
3/5V3000GL	3	5V	7620	300.00	6.40	14.10
3/5V3150GL	3	5V	8001	315.00	6.72	14.81
3/5V3350GL	3	5V	8509	335.00	7.14	15.75
3/5V3550GL	3	5V	9017	355.00	7.57	16.69
4/5V600GL	4	5V	1524	60.00	1.71	3.76
4/5V630GL	4	5V	1600	63.00	1.79	3.95
4/5V670GL	4	5V	1702	67.00	1.90	4.20
4/5V710GL	4	5V	1803	71.00	2.02	4.45
4/5V750GL	4	5V	1905	75.00	2.13	4.70
4/5V800GL	4	5V	2032	80.00	2.27	5.01
4/5V850GL	4	5V	2159	85.00	2.42	5.33
4/5V900GL	4	5V	2286	90.00	2.56	5.64
4/5V950GL	4	5V	2413	95.00	2.70	5.95
4/5V1000GL	4	5V	2540	100.00	2.84	6.27
4/5V1060GL	4	5V	2692	106.00	3.01	6.64
4/5V1120GL	4	5V	2845	112.00	3.18	7.02
4/5V1180GL	4	5V	2997	118.00	3.35	7.40
4/5V1200GL	4	5V	3048	120.00	3.41	7.52
4/5V1210GL	4	5V	3073	121.00	3.44	7.58
4/5V1250GL	4	5V	3175	125.00	3.55	7.83
4/5V1320GL	4	5V	3353	132.00	3.75	8.27
4/5V1400GL	4	5V	3556	140.00	3.98	8.78
4/5V1500GL	4	5V	3810	150.00	4.26	9.40
4/5V1600GL	4	5V	4064	160.00	4.55	10.03
4/5V1700GL	4	5V	4318	170.00	4.83	10.66
4/5V1800GL	4	5V	4572	180.00	5.12	11.28




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
4/5V1900GL	4	5V	4826	190.00	5.40	11.91
4/5V2000GL	4	5V	5080	200.00	5.69	12.54
4/5V2120GL	4	5V	5385	212.00	6.03	13.29
4/5V2240GL	4	5V	5690	224.00	6.37	14.04
4/5V2360GL	4	5V	5994	236.00	6.71	14.79
4/5V2500GL	4	5V	6350	250.00	7.11	15.67
4/5V2650GL	4	5V	6731	265.00	7.53	16.61
4/5V2800GL	4	5V	7112	280.00	7.96	17.55
4/5V3000GL	4	5V	7620	300.00	8.53	18.80
4/5V3150GL	4	5V	8001	315.00	8.96	19.74
4/5V3350GL	4	5V	8509	335.00	9.52	21.00
4/5V3550GL	4	5V	9017	355.00	10.09	22.25
5/5V600GL	5	5V	1524	60.00	2.13	4.70
5/5V630GL	5	5V	1600	63.00	2.24	4.94
5/5V670GL	5	5V	1702	67.00	2.38	5.25
5/5V710GL	5	5V	1803	71.00	2.52	5.56
5/5V750GL	5	5V	1905	75.00	2.67	5.88
5/5V800GL	5	5V	2032	80.00	2.84	6.27
5/5V850GL	5	5V	2159	85.00	3.02	6.66
5/5V900GL	5	5V	2286	90.00	3.20	7.05
5/5V950GL	5	5V	2413	95.00	3.38	7.44
5/5V1000GL	5	5V	2540	100.00	3.55	7.83
5/5V1060GL	5	5V	2692	106.00	3.77	8.30
5/5V1120GL	5	5V	2845	112.00	3.98	8.78
5/5V1180GL	5	5V	2997	118.00	4.19	9.25
5/5V1200GL	5	5V	3048	120.00	4.26	9.40
5/5V1210GL	5	5V	3073	121.00	4.30	9.48
5/5V1250GL	5	5V	3175	125.00	4.44	9.79
5/5V1320GL	5	5V	3353	132.00	4.69	10.34
5/5V1400GL	5	5V	3556	140.00	4.98	10.97
5/5V1500GL	5	5V	3810	150.00	5.33	11.75
5/5V1600GL	5	5V	4064	160.00	5.69	12.54
5/5V1700GL	5	5V	4318	170.00	6.04	13.32
5/5V1800GL	5	5V	4572	180.00	6.40	14.10




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
5/5V1900GL	5	5V	4826	190.00	6.75	14.89
5/5V2000GL	5	5V	5080	200.00	7.11	15.67
5/5V2120GL	5	5V	5385	212.00	7.53	16.61
5/5V2240GL	5	5V	5690	224.00	7.96	17.55
5/5V2360GL	5	5V	5994	236.00	8.39	18.49
5/5V2500GL	5	5V	6350	250.00	8.88	19.59
5/5V2650GL	5	5V	6731	265.00	9.42	20.76
5/5V2800GL	5	5V	7112	280.00	9.95	21.94
5/5V3000GL	5	5V	7620	300.00	10.66	23.50
5/5V3150GL	5	5V	8001	315.00	11.19	24.68
5/5V3350GL	5	5V	8509	335.00	11.91	26.25
5/5V3550GL	5	5V	9017	355.00	12.62	27.81
16/5V600GL	16	5V	1524	60.00	6.82	15.04
26/5V3150GL	26	5V	8001	315.00	58.21	128.34
26/5V3350GL	26	5V	8509	335.00	61.91	136.48
26/5V3550GL	26	5V	9017	355.00	65.60	144.63
32/5V630GL	32	5V	1600	63.00	14.33	31.59
32/5V670GL	32	5V	1702	67.00	15.24	33.60
32/5V710GL	32	5V	1803	71.00	16.15	35.60
32/5V750GL	32	5V	1905	75.00	17.06	37.61
32/5V800GL	32	5V	2032	80.00	18.20	40.11
32/5V850GL	32	5V	2159	85.00	19.33	42.62
32/5V900GL	32	5V	2286	90.00	20.47	45.13
32/5V950GL	32	5V	2413	95.00	21.61	47.64
32/5V1000GL	32	5V	2540	100.00	22.74	50.14
32/5V1060GL	32	5V	2692	106.00	24.11	53.15
32/5V1120GL	32	5V	2845	112.00	25.47	56.16
32/5V1180GL	32	5V	2997	118.00	26.84	59.17
32/5V1200GL	32	5V	3048	120.00	27.29	60.17
32/5V1210GL	32	5V	3073	121.00	27.52	60.67
32/5V1250GL	32	5V	3175	125.00	28.43	62.68
32/5V1320GL	32	5V	3353	132.00	30.02	66.19
32/5V1400GL	32	5V	3556	140.00	31.84	70.20
32/5V1500GL	32	5V	3810	150.00	34.12	75.21




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
32/5V1600GL	32	5V	4064	160.00	36.39	80.23
32/5V1700GL	32	5V	4318	170.00	38.67	85.24
32/5V1800GL	32	5V	4572	180.00	40.94	90.26
32/5V1900GL	32	5V	4826	190.00	43.21	95.27
32/5V2000GL	32	5V	5080	200.00	45.49	100.29
32/5V2120GL	32	5V	5385	212.00	48.22	106.30
32/5V2240GL	32	5V	5690	224.00	50.95	112.32
32/5V2360GL	32	5V	5994	236.00	53.68	118.34
32/5V2500GL	32	5V	6350	250.00	56.86	125.36
32/5V2650GL	32	5V	6731	265.00	60.27	132.88
32/5V2800GL	32	5V	7112	280.00	63.68	140.40
32/5V3000GL	32	5V	7620	300.00	68.23	150.43
2/8V1120GL	2	8V	2845	112.00	3.78	8.33
2/8V1180GL	2	8V	2997	118.00	3.98	8.78
2/8V1250GL	2	8V	3175	125.00	4.22	9.30
2/8V1320GL	2	8V	3353	132.00	4.45	9.82
2/8V1400GL	2	8V	3556	140.00	4.72	10.42
2/8V1500GL	2	8V	3810	150.00	5.06	11.16
2/8V1600GL	2	8V	4064	160.00	5.40	11.90
2/8V1700GL	2	8V	4318	170.00	5.74	12.65
2/8V1800GL	2	8V	4572	180.00	6.07	13.39
2/8V1900GL	2	8V	4826	190.00	6.41	14.14
2/8V2000GL	2	8V	5080	200.00	6.75	14.88
2/8V2120GL	2	8V	5385	212.00	7.15	15.77
2/8V2240GL	2	8V	5690	224.00	7.56	16.67
2/8V2360GL	2	8V	5994	236.00	7.96	17.56
2/8V2500GL	2	8V	6350	250.00	8.44	18.60
2/8V2650GL	2	8V	6731	265.00	8.94	19.72
2/8V2800GL	2	8V	7112	280.00	9.45	20.83
2/8V3000GL	2	8V	7620	300.00	10.12	22.32
2/8V3150GL	2	8V	8001	315.00	10.63	23.44
2/8V3350GL	2	8V	8509	335.00	11.30	24.92
2/8V3550GL	2	8V	9017	355.00	11.98	26.41
2/8V3750GL	2	8V	9525	375.00	12.65	27.90




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/8V4000GL	2	8V	10160	400.00	13.50	29.76
2/8V4250GL	2	8V	10795	425.00	14.34	31.62
2/8V4500GL	2	8V	11430	450.00	15.19	33.48
2/8V4750GL	2	8V	12065	475.00	16.03	35.34
2/8V5000GL	2	8V	12700	500.00	16.87	37.20
2/8V5600GL	2	8V	14224	560.00	18.90	41.66
2/8V6000GL	2	8V	15240	600.00	20.25	44.64
3/8V1120GL	3	8V	2845	112.00	5.67	12.50
3/8V1180GL	3	8V	2997	118.00	5.97	13.17
3/8V1250GL	3	8V	3175	125.00	6.33	13.95
3/8V1320GL	3	8V	3353	132.00	6.68	14.73
3/8V1400GL	3	8V	3556	140.00	7.09	15.62
3/8V1500GL	3	8V	3810	150.00	7.59	16.74
3/8V1600GL	3	8V	4064	160.00	8.10	17.86
3/8V1700GL	3	8V	4318	170.00	8.61	18.97
3/8V1800GL	3	8V	4572	180.00	9.11	20.09
3/8V1900GL	3	8V	4826	190.00	9.62	21.20
3/8V2000GL	3	8V	5080	200.00	10.12	22.32
3/8V2120GL	3	8V	5385	212.00	10.73	23.66
3/8V2240GL	3	8V	5690	224.00	11.34	25.00
3/8V2360GL	3	8V	5994	236.00	11.95	26.34
3/8V2500GL	3	8V	6350	250.00	12.65	27.90
3/8V2650GL	3	8V	6731	265.00	13.41	29.57
3/8V2800GL	3	8V	7112	280.00	14.17	31.25
3/8V3000GL	3	8V	7620	300.00	15.19	33.48
3/8V3150GL	3	8V	8001	315.00	15.95	35.15
3/8V3350GL	3	8V	8509	335.00	16.96	37.38
3/8V3550GL	3	8V	9017	355.00	17.97	39.62
3/8V3750GL	3	8V	9525	375.00	18.98	41.85
3/8V4000GL	3	8V	10160	400.00	20.25	44.64
3/8V4250GL	3	8V	10795	425.00	21.51	47.43
3/8V4500GL	3	8V	11430	450.00	22.78	50.22
3/8V4750GL	3	8V	12065	475.00	24.04	53.01
3/8V5000GL	3	8V	12700	500.00	25.31	55.80




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
3/8V5600GL	3	8V	14224	560.00	28.35	62.49
3/8V6000GL	3	8V	15240	600.00	30.37	66.96
4/8V1120GL	4	8V	2845	112.00	7.56	16.67
4/8V1180GL	4	8V	2997	118.00	7.96	17.56
4/8V1250GL	4	8V	3175	125.00	8.44	18.60
4/8V1320GL	4	8V	3353	132.00	8.91	19.64
4/8V1400GL	4	8V	3556	140.00	9.45	20.83
4/8V1500GL	4	8V	3810	150.00	10.12	22.32
4/8V1600GL	4	8V	4064	160.00	10.80	23.81
4/8V1700GL	4	8V	4318	170.00	11.47	25.30
4/8V1800GL	4	8V	4572	180.00	12.15	26.78
4/8V1900GL	4	8V	4826	190.00	12.82	28.27
4/8V2000GL	4	8V	5080	200.00	13.50	29.76
4/8V2120GL	4	8V	5385	212.00	14.31	31.54
4/8V2240GL	4	8V	5690	224.00	15.12	33.33
4/8V2360GL	4	8V	5994	236.00	15.93	35.12
4/8V2500GL	4	8V	6350	250.00	16.87	37.20
4/8V2650GL	4	8V	6731	265.00	17.89	39.43
4/8V2800GL	4	8V	7112	280.00	18.90	41.66
4/8V3000GL	4	8V	7620	300.00	20.25	44.64
4/8V3150GL	4	8V	8001	315.00	21.26	46.87
4/8V3350GL	4	8V	8509	335.00	22.61	49.85
4/8V3550GL	4	8V	9017	355.00	23.96	52.82
4/8V3750GL	4	8V	9525	375.00	25.31	55.80
4/8V4000GL	4	8V	10160	400.00	27.00	59.52
4/8V4250GL	4	8V	10795	425.00	28.68	63.24
4/8V4500GL	4	8V	11430	450.00	30.37	66.96
4/8V4750GL	4	8V	12065	475.00	32.06	70.68
4/8V5000GL	4	8V	12700	500.00	33.75	74.40
4/8V5600GL	4	8V	14224	560.00	37.80	83.33
4/8V6000GL	4	8V	15240	600.00	40.50	89.28
5/8V1120GL	5	8V	2845	112.00	9.45	20.83
5/8V1180GL	5	8V	2997	118.00	9.96	21.95
5/8V1250GL	5	8V	3175	125.00	10.55	23.25




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
5/8V1320GL	5	8V	3353	132.00	11.14	24.55
5/8V1400GL	5	8V	3556	140.00	11.81	26.04
5/8V1500GL	5	8V	3810	150.00	12.65	27.90
5/8V1600GL	5	8V	4064	160.00	13.50	29.76
5/8V1700GL	5	8V	4318	170.00	14.34	31.62
5/8V1800GL	5	8V	4572	180.00	15.19	33.48
5/8V1900GL	5	8V	4826	190.00	16.03	35.34
5/8V2000GL	5	8V	5080	200.00	16.87	37.20
5/8V2120GL	5	8V	5385	212.00	17.89	39.43
5/8V2240GL	5	8V	5690	224.00	18.90	41.66
5/8V2360GL	5	8V	5994	236.00	19.91	43.89
5/8V2500GL	5	8V	6350	250.00	21.09	46.50
5/8V2650GL	5	8V	6731	265.00	22.36	49.29
5/8V2800GL	5	8V	7112	280.00	23.62	52.08
5/8V3000GL	5	8V	7620	300.00	25.31	55.80
5/8V3150GL	5	8V	8001	315.00	26.58	58.59
5/8V3350GL	5	8V	8509	335.00	28.26	62.31
5/8V3550GL	5	8V	9017	355.00	29.95	66.03
5/8V3750GL	5	8V	9525	375.00	31.64	69.75
5/8V4000GL	5	8V	10160	400.00	33.75	74.40
5/8V4250GL	5	8V	10795	425.00	35.86	79.05
5/8V4500GL	5	8V	11430	450.00	37.96	83.70
5/8V4750GL	5	8V	12065	475.00	40.07	88.35
5/8V5000GL	5	8V	12700	500.00	42.18	93.00
5/8V5600GL	5	8V	14224	560.00	47.24	104.16
5/8V6000GL	5	8V	15240	600.00	50.62	111.60
16/8V1120GL	16	8V	2845	112.00	30.24	66.66
16/8V1180GL	16	8V	2997	118.00	31.86	70.23
16/8V1250GL	16	8V	3175	125.00	33.75	74.40
16/8V1320GL	16	8V	3353	132.00	35.64	78.56
16/8V1400GL	16	8V	3556	140.00	37.80	83.33
16/8V1500GL	16	8V	3810	150.00	40.50	89.28
16/8V1600GL	16	8V	4064	160.00	43.19	95.23
16/8V1700GL	16	8V	4318	170.00	45.89	101.18




MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
16/8V1800GL	16	8V	4572	180.00	48.59	107.13
16/8V1900GL	16	8V	4826	190.00	51.29	113.08
16/8V2000GL	16	8V	5080	200.00	53.99	119.04
16/8V2120GL	16	8V	5385	212.00	57.23	126.18
16/8V2240GL	16	8V	5690	224.00	60.47	133.32
16/8V2360GL	16	8V	5994	236.00	63.71	140.46
16/8V2500GL	16	8V	6350	250.00	67.49	148.79
16/8V2650GL	16	8V	6731	265.00	71.54	157.72
16/8V2800GL	16	8V	7112	280.00	75.59	166.65
16/8V3000GL	16	8V	7620	300.00	80.99	178.55
16/8V3150GL	16	8V	8001	315.00	85.04	187.48
16/8V3350GL	16	8V	8509	335.00	90.44	199.38
16/8V3550GL	16	8V	9017	355.00	95.84	211.29
16/8V3750GL	16	8V	9525	375.00	101.24	223.19
16/8V4000GL	16	8V	10160	400.00	107.99	238.07
16/8V4250GL	16	8V	10795	425.00	114.74	252.95
16/8V4500GL	16	8V	11430	450.00	121.49	267.83
16/8V4750GL	16	8V	12065	475.00	128.24	282.71
16/8V5000GL	16	8V	12700	500.00	134.98	297.59
16/8V5600GL	16	8V	14224	560.00	151.18	333.30
16/8V6000GL	16	8V	15240	600.00	161.98	357.11



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

V-Belt

Part Number Description: **2/SPA1500GL**

2/: Number of ribs

SPA: Profile

1500: Datum Length (mm)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, Rubber Impregnated

- Abrasion, wear and oil resistance
- Prevents vibrations and belt turn-over

Fabric Cover: PET/Cotton, Rubber Impregnated

- Abrasion, wear and oil resistance
- Static conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber Blend

- High resistance to bending stress
- Superior oil and heat resistance
- Temperature range: -31°F (-35°C) to 160°F (70°C)

RLT: Restricted length tolerance, matching set according to ISO 4184

Wedge Profile (Metric): Up to 3 times the power transmission capacity of classical V profiles (Z, A, B, C, D, E)

Markets and Applications:


Designed for high horsepower and shock load applications, these industrial banded belts are primarily employed on applications where multiple belts have the tendency to vibrate, turn over or come off pulleys when subjected to fluctuating load tensions and high horsepower.

The Dayco GOLD LABEL industrial banded belt is available in both wrapped molded construction and raw edge versions and provides the same oil and heat resistant characteristics as the Dayco GOLD LABEL single belts with the addition of a fabric rubber top band for multiple belt stability.



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/SPZ1500GL	2	SPZ	1500	59.06	0.38	0.84
2/SPZ1600GL	2	SPZ	1600	62.99	0.41	0.90
2/SPZ1700GL	2	SPZ	1700	66.93	0.43	0.96
2/SPZ1800GL	2	SPZ	1800	70.87	0.46	1.01
2/SPZ1900GL	2	SPZ	1900	74.80	0.49	1.07
2/SPZ2000GL	2	SPZ	2000	78.74	0.51	1.13
2/SPZ2120GL	2	SPZ	2120	83.46	0.54	1.19
2/SPZ2240GL	2	SPZ	2240	88.19	0.57	1.26
2/SPZ2360GL	2	SPZ	2360	92.91	0.60	1.33
2/SPZ2500GL	2	SPZ	2500	98.43	0.64	1.41
2/SPZ2650GL	2	SPZ	2650	104.33	0.68	1.49
2/SPZ2800GL	2	SPZ	2800	110.24	0.72	1.58
2/SPZ3000GL	2	SPZ	3000	118.11	0.77	1.69
2/SPZ3150GL	2	SPZ	3150	124.02	0.80	1.77
2/SPZ3350GL	2	SPZ	3350	131.89	0.86	1.89
2/SPZ3550GL	2	SPZ	3550	139.76	0.91	2.00
3/SPZ1500GL	3	SPZ	1500	59.06	0.57	1.27
3/SPZ1600GL	3	SPZ	1600	62.99	0.61	1.35
3/SPZ1700GL	3	SPZ	1700	66.93	0.65	1.44
3/SPZ1800GL	3	SPZ	1800	70.87	0.69	1.52
3/SPZ1900GL	3	SPZ	1900	74.80	0.73	1.60
3/SPZ2000GL	3	SPZ	2000	78.74	0.77	1.69
3/SPZ2120GL	3	SPZ	2120	83.46	0.81	1.79
3/SPZ2240GL	3	SPZ	2240	88.19	0.86	1.89
3/SPZ2360GL	3	SPZ	2360	92.91	0.90	1.99
3/SPZ2500GL	3	SPZ	2500	98.43	0.96	2.11
3/SPZ2650GL	3	SPZ	2650	104.33	1.02	2.24
3/SPZ2800GL	3	SPZ	2800	110.24	1.07	2.36
3/SPZ3000GL	3	SPZ	3000	118.11	1.15	2.53
3/SPZ3150GL	3	SPZ	3150	124.02	1.21	2.66
3/SPZ3350GL	3	SPZ	3350	131.89	1.28	2.83
3/SPZ3550GL	3	SPZ	3550	139.76	1.36	3.00
4/SPZ1500GL	4	SPZ	1500	59.06	0.77	1.69
4/SPZ1600GL	4	SPZ	1600	62.99	0.82	1.80



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/SPZ1700GL	4	SPZ	1700	66.93	0.87	1.91
4/SPZ1800GL	4	SPZ	1800	70.87	0.92	2.03
4/SPZ1900GL	4	SPZ	1900	74.80	0.97	2.14
4/SPZ2000GL	4	SPZ	2000	78.74	1.02	2.25
4/SPZ2120GL	4	SPZ	2120	83.46	1.08	2.39
4/SPZ2240GL	4	SPZ	2240	88.19	1.14	2.52
4/SPZ2360GL	4	SPZ	2360	92.91	1.21	2.66
4/SPZ2500GL	4	SPZ	2500	98.43	1.28	2.82
4/SPZ2650GL	4	SPZ	2650	104.33	1.35	2.98
4/SPZ2800GL	4	SPZ	2800	110.24	1.43	3.15
4/SPZ3000GL	4	SPZ	3000	118.11	1.53	3.38
4/SPZ3150GL	4	SPZ	3150	124.02	1.61	3.55
4/SPZ3350GL	4	SPZ	3350	131.89	1.71	3.77
4/SPZ3550GL	4	SPZ	3550	139.76	1.81	4.00
5/SPZ1500GL	5	SPZ	1500	59.06	0.96	2.11
5/SPZ1600GL	5	SPZ	1600	62.99	1.02	2.25
5/SPZ1700GL	5	SPZ	1700	66.93	1.09	2.39
5/SPZ1800GL	5	SPZ	1800	70.87	1.15	2.53
5/SPZ1900GL	5	SPZ	1900	74.80	1.21	2.67
5/SPZ2000GL	5	SPZ	2000	78.74	1.28	2.82
5/SPZ2120GL	5	SPZ	2120	83.46	1.35	2.98
5/SPZ2240GL	5	SPZ	2240	88.19	1.43	3.15
5/SPZ2360GL	5	SPZ	2360	92.91	1.51	3.32
5/SPZ2500GL	5	SPZ	2500	98.43	1.60	3.52
5/SPZ2650GL	5	SPZ	2650	104.33	1.69	3.73
5/SPZ2800GL	5	SPZ	2800	110.24	1.79	3.94
5/SPZ3000GL	5	SPZ	3000	118.11	1.92	4.22
5/SPZ3150GL	5	SPZ	3150	124.02	2.01	4.43
5/SPZ3350GL	5	SPZ	3350	131.89	2.14	4.72
5/SPZ3550GL	5	SPZ	3550	139.76	2.27	5.00
25/SPZ1500GL	25	SPZ	1500	59.06	4.79	10.56
25/SPZ1600GL	25	SPZ	1600	62.99	5.11	11.26
25/SPZ1700GL	25	SPZ	1700	66.93	5.43	11.96
25/SPZ1800GL	25	SPZ	1800	70.87	5.75	12.67



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
25/SPZ1900GL	25	SPZ	1900	74.80	6.07	13.37
25/SPZ2000GL	25	SPZ	2000	78.74	6.38	14.08
25/SPZ2120GL	25	SPZ	2120	83.46	6.77	14.92
25/SPZ2240GL	25	SPZ	2240	88.19	7.15	15.76
25/SPZ2360GL	25	SPZ	2360	92.91	7.53	16.61
25/SPZ2500GL	25	SPZ	2500	98.43	7.98	17.59
25/SPZ2650GL	25	SPZ	2650	104.33	8.46	18.65
25/SPZ2800GL	25	SPZ	2800	110.24	8.94	19.71
25/SPZ3000GL	25	SPZ	3000	118.11	9.58	21.11
25/SPZ3150GL	25	SPZ	3150	124.02	10.06	22.17
25/SPZ3350GL	25	SPZ	3350	131.89	10.69	23.58
25/SPZ3550GL	25	SPZ	3550	139.76	11.33	24.98
2/SPA1500GL	2	SPA	1500	59.06	0.51	1.12
2/SPA1600GL	2	SPA	1600	62.99	0.54	1.20
2/SPA1700GL	2	SPA	1700	66.93	0.58	1.27
2/SPA1800GL	2	SPA	1800	70.87	0.61	1.35
2/SPA1900GL	2	SPA	1900	74.80	0.65	1.42
2/SPA2000GL	2	SPA	2000	78.74	0.68	1.50
2/SPA2120GL	2	SPA	2120	83.46	0.72	1.59
2/SPA2240GL	2	SPA	2240	88.19	0.76	1.68
2/SPA2360GL	2	SPA	2360	92.91	0.80	1.77
2/SPA2500GL	2	SPA	2500	98.43	0.85	1.87
2/SPA2650GL	2	SPA	2650	104.33	0.90	1.99
2/SPA2800GL	2	SPA	2800	110.24	0.95	2.10
2/SPA3000GL	2	SPA	3000	118.11	1.02	2.25
2/SPA3150GL	2	SPA	3150	124.02	1.07	2.36
2/SPA3350GL	2	SPA	3350	131.89	1.14	2.51
2/SPA3550GL	2	SPA	3550	139.76	1.21	2.66
2/SPA3750GL	2	SPA	3750	147.64	1.28	2.81
2/SPA4000GL	2	SPA	4000	157.48	1.36	3.00
2/SPA4250GL	2	SPA	4250	167.32	1.45	3.19
2/SPA4500GL	2	SPA	4500	177.17	1.53	3.37
3/SPA1500GL	3	SPA	1500	59.06	0.77	1.69
3/SPA1600GL	3	SPA	1600	62.99	0.82	1.80



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/SPA1700GL	3	SPA	1700	66.93	0.87	1.91
3/SPA1800GL	3	SPA	1800	70.87	0.92	2.02
3/SPA1900GL	3	SPA	1900	74.80	0.97	2.14
3/SPA2000GL	3	SPA	2000	78.74	1.02	2.25
3/SPA2120GL	3	SPA	2120	83.46	1.08	2.38
3/SPA2240GL	3	SPA	2240	88.19	1.14	2.52
3/SPA2360GL	3	SPA	2360	92.91	1.20	2.65
3/SPA2500GL	3	SPA	2500	98.43	1.28	2.81
3/SPA2650GL	3	SPA	2650	104.33	1.35	2.98
3/SPA2800GL	3	SPA	2800	110.24	1.43	3.15
3/SPA3000GL	3	SPA	3000	118.11	1.53	3.37
3/SPA3150GL	3	SPA	3150	124.02	1.61	3.54
3/SPA3350GL	3	SPA	3350	131.89	1.71	3.77
3/SPA3550GL	3	SPA	3550	139.76	1.81	3.99
3/SPA3750GL	3	SPA	3750	147.64	1.91	4.22
3/SPA4000GL	3	SPA	4000	157.48	2.04	4.50
3/SPA4250GL	3	SPA	4250	167.32	2.17	4.78
3/SPA4500GL	3	SPA	4500	177.17	2.30	5.06
4/SPA1500GL	4	SPA	1500	59.06	1.02	2.25
4/SPA1600GL	4	SPA	1600	62.99	1.09	2.40
4/SPA1700GL	4	SPA	1700	66.93	1.16	2.55
4/SPA1800GL	4	SPA	1800	70.87	1.22	2.70
4/SPA1900GL	4	SPA	1900	74.80	1.29	2.85
4/SPA2000GL	4	SPA	2000	78.74	1.36	3.00
4/SPA2120GL	4	SPA	2120	83.46	1.44	3.18
4/SPA2240GL	4	SPA	2240	88.19	1.52	3.36
4/SPA2360GL	4	SPA	2360	92.91	1.61	3.54
4/SPA2500GL	4	SPA	2500	98.43	1.70	3.75
4/SPA2650GL	4	SPA	2650	104.33	1.80	3.97
4/SPA2800GL	4	SPA	2800	110.24	1.90	4.20
4/SPA3000GL	4	SPA	3000	118.11	2.04	4.50
4/SPA3150GL	4	SPA	3150	124.02	2.14	4.72
4/SPA3350GL	4	SPA	3350	131.89	2.28	5.02
4/SPA3550GL	4	SPA	3550	139.76	2.41	5.32



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/SPA3750GL	4	SPA	3750	147.64	2.55	5.62
4/SPA4000GL	4	SPA	4000	157.48	2.72	6.00
4/SPA4250GL	4	SPA	4250	167.32	2.89	6.37
4/SPA4500GL	4	SPA	4500	177.17	3.06	6.75
5/SPA1500GL	5	SPA	1500	59.06	1.28	2.81
5/SPA1600GL	5	SPA	1600	62.99	1.36	3.00
5/SPA1700GL	5	SPA	1700	66.93	1.45	3.19
5/SPA1800GL	5	SPA	1800	70.87	1.53	3.37
5/SPA1900GL	5	SPA	1900	74.80	1.62	3.56
5/SPA2000GL	5	SPA	2000	78.74	1.70	3.75
5/SPA2120GL	5	SPA	2120	83.46	1.80	3.97
5/SPA2240GL	5	SPA	2240	88.19	1.90	4.20
5/SPA2360GL	5	SPA	2360	92.91	2.01	4.42
5/SPA2500GL	5	SPA	2500	98.43	2.13	4.69
5/SPA2650GL	5	SPA	2650	104.33	2.25	4.97
5/SPA2800GL	5	SPA	2800	110.24	2.38	5.25
5/SPA3000GL	5	SPA	3000	118.11	2.55	5.62
5/SPA3150GL	5	SPA	3150	124.02	2.68	5.90
5/SPA3350GL	5	SPA	3350	131.89	2.85	6.28
5/SPA3550GL	5	SPA	3550	139.76	3.02	6.65
5/SPA3750GL	5	SPA	3750	147.64	3.19	7.03
5/SPA4000GL	5	SPA	4000	157.48	3.40	7.50
5/SPA4250GL	5	SPA	4250	167.32	3.61	7.97
5/SPA4500GL	5	SPA	4500	177.17	3.83	8.43
20/SPA1500GL	20	SPA	1500	59.06	5.10	11.25
20/SPA1600GL	20	SPA	1600	62.99	5.44	12.00
20/SPA1700GL	20	SPA	1700	66.93	5.78	12.74
20/SPA1800GL	20	SPA	1800	70.87	6.12	13.49
20/SPA1900GL	20	SPA	1900	74.80	6.46	14.24
20/SPA2000GL	20	SPA	2000	78.74	6.80	14.99
20/SPA2120GL	20	SPA	2120	83.46	7.21	15.89
30/SPA2240GL	30	SPA	2240	88.19	11.43	25.19
30/SPA2360GL	30	SPA	2360	92.91	12.04	26.54
30/SPA2500GL	30	SPA	2500	98.43	12.75	28.11



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
30/SPA2650GL	30	SPA	2650	104.33	13.52	29.80
30/SPA2800GL	30	SPA	2800	110.24	14.28	31.49
30/SPA3000GL	30	SPA	3000	118.11	15.30	33.74
30/SPA3150GL	30	SPA	3150	124.02	16.07	35.42
30/SPA3350GL	30	SPA	3350	131.89	17.09	37.67
30/SPA3550GL	30	SPA	3550	139.76	18.11	39.92
30/SPA3750GL	30	SPA	3750	147.64	19.13	42.17
30/SPA4000GL	30	SPA	4000	157.48	20.40	44.98
30/SPA4250GL	30	SPA	4250	167.32	21.68	47.79
30/SPA4500GL	30	SPA	4500	177.17	22.95	50.60
2/SPB2000GL	2	SPB	2000	78.74	1.03	2.28
2/SPB2120GL	2	SPB	2120	83.46	1.09	2.41
2/SPB2240GL	2	SPB	2240	88.19	1.16	2.55
2/SPB2360GL	2	SPB	2360	92.91	1.22	2.69
2/SPB2500GL	2	SPB	2500	98.43	1.29	2.85
2/SPB2650GL	2	SPB	2650	104.33	1.37	3.02
2/SPB2800GL	2	SPB	2800	110.24	1.45	3.19
2/SPB3000GL	2	SPB	3000	118.11	1.55	3.42
2/SPB3150GL	2	SPB	3150	124.02	1.63	3.59
2/SPB3350GL	2	SPB	3350	131.89	1.73	3.81
2/SPB3550GL	2	SPB	3550	139.76	1.83	4.04
2/SPB3750GL	2	SPB	3750	147.64	1.94	4.27
2/SPB4000GL	2	SPB	4000	157.48	2.07	4.55
2/SPB4250GL	2	SPB	4250	167.32	2.19	4.84
2/SPB4500GL	2	SPB	4500	177.17	2.32	5.12
2/SPB4750GL	2	SPB	4750	187.01	2.45	5.41
2/SPB5000GL	2	SPB	5000	196.85	2.58	5.69
2/SPB5300GL	2	SPB	5300	208.66	2.74	6.03
2/SPB5600GL	2	SPB	5600	220.47	2.89	6.38
2/SPB6000GL	2	SPB	6000	236.22	3.10	6.83
2/SPB6300GL	2	SPB	6300	248.03	3.25	7.17
2/SPB6700GL	2	SPB	6700	263.78	3.46	7.63
2/SPB7100GL	2	SPB	7100	279.53	3.67	8.08
2/SPB7500GL	2	SPB	7500	295.28	3.87	8.54



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/SPB8000GL	2	SPB	8000	314.96	4.13	9.11
3/SPB2000GL	3	SPB	2000	78.74	1.55	3.42
3/SPB2120GL	3	SPB	2120	83.46	1.64	3.62
3/SPB2240GL	3	SPB	2240	88.19	1.74	3.83
3/SPB2360GL	3	SPB	2360	92.91	1.83	4.03
3/SPB2500GL	3	SPB	2500	98.43	1.94	4.27
3/SPB2650GL	3	SPB	2650	104.33	2.05	4.53
3/SPB2800GL	3	SPB	2800	110.24	2.17	4.78
3/SPB3000GL	3	SPB	3000	118.11	2.32	5.12
3/SPB3150GL	3	SPB	3150	124.02	2.44	5.38
3/SPB3350GL	3	SPB	3350	131.89	2.59	5.72
3/SPB3550GL	3	SPB	3550	139.76	2.75	6.06
3/SPB3750GL	3	SPB	3750	147.64	2.90	6.40
3/SPB4000GL	3	SPB	4000	157.48	3.10	6.83
3/SPB4250GL	3	SPB	4250	167.32	3.29	7.26
3/SPB4500GL	3	SPB	4500	177.17	3.49	7.68
3/SPB4750GL	3	SPB	4750	187.01	3.68	8.11
3/SPB5000GL	3	SPB	5000	196.85	3.87	8.54
3/SPB5300GL	3	SPB	5300	208.66	4.11	9.05
3/SPB5600GL	3	SPB	5600	220.47	4.34	9.56
3/SPB6000GL	3	SPB	6000	236.22	4.65	10.25
3/SPB6300GL	3	SPB	6300	248.03	4.88	10.76
3/SPB6700GL	3	SPB	6700	263.78	5.19	11.44
3/SPB7100GL	3	SPB	7100	279.53	5.50	12.13
3/SPB7500GL	3	SPB	7500	295.28	5.81	12.81
3/SPB8000GL	3	SPB	8000	314.96	6.20	13.66
4/SPB2000GL	4	SPB	2000	78.74	2.07	4.55
4/SPB2120GL	4	SPB	2120	83.46	2.19	4.83
4/SPB2240GL	4	SPB	2240	88.19	2.31	5.10
4/SPB2360GL	4	SPB	2360	92.91	2.44	5.37
4/SPB2500GL	4	SPB	2500	98.43	2.58	5.69
4/SPB2650GL	4	SPB	2650	104.33	2.74	6.03
4/SPB2800GL	4	SPB	2800	110.24	2.89	6.38
4/SPB3000GL	4	SPB	3000	118.11	3.10	6.83



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL®



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/SPB3150GL	4	SPB	3150	124.02	3.25	7.17
4/SPB3350GL	4	SPB	3350	131.89	3.46	7.63
4/SPB3550GL	4	SPB	3550	139.76	3.67	8.08
4/SPB3750GL	4	SPB	3750	147.64	3.87	8.54
4/SPB4000GL	4	SPB	4000	157.48	4.13	9.11
4/SPB4250GL	4	SPB	4250	167.32	4.39	9.68
4/SPB4500GL	4	SPB	4500	177.17	4.65	10.25
4/SPB4750GL	4	SPB	4750	187.01	4.91	10.82
4/SPB5000GL	4	SPB	5000	196.85	5.16	11.38
4/SPB5300GL	4	SPB	5300	208.66	5.47	12.07
4/SPB5600GL	4	SPB	5600	220.47	5.78	12.75
4/SPB6000GL	4	SPB	6000	236.22	6.20	13.66
4/SPB6300GL	4	SPB	6300	248.03	6.51	14.35
4/SPB6700GL	4	SPB	6700	263.78	6.92	15.26
4/SPB7100GL	4	SPB	7100	279.53	7.33	16.17
4/SPB7500GL	4	SPB	7500	295.28	7.75	17.08
4/SPB8000GL	4	SPB	8000	314.96	8.26	18.22
5/SPB2000GL	5	SPB	2000	78.74	2.58	5.69
5/SPB2120GL	5	SPB	2120	83.46	2.74	6.03
5/SPB2240GL	5	SPB	2240	88.19	2.89	6.38
5/SPB2360GL	5	SPB	2360	92.91	3.05	6.72
5/SPB2500GL	5	SPB	2500	98.43	3.23	7.12
5/SPB2650GL	5	SPB	2650	104.33	3.42	7.54
5/SPB2800GL	5	SPB	2800	110.24	3.61	7.97
5/SPB3000GL	5	SPB	3000	118.11	3.87	8.54
5/SPB3150GL	5	SPB	3150	124.02	4.07	8.97
5/SPB3350GL	5	SPB	3350	131.89	4.32	9.53
5/SPB3550GL	5	SPB	3550	139.76	4.58	10.10
5/SPB3750GL	5	SPB	3750	147.64	4.84	10.67
5/SPB4000GL	5	SPB	4000	157.48	5.16	11.38
5/SPB4250GL	5	SPB	4250	167.32	5.49	12.10
5/SPB4500GL	5	SPB	4500	177.17	5.81	12.81
5/SPB4750GL	5	SPB	4750	187.01	6.13	13.52
5/SPB5000GL	5	SPB	5000	196.85	6.46	14.23



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
5/SPB5300GL	5	SPB	5300	208.66	6.84	15.09
5/SPB5600GL	5	SPB	5600	220.47	7.23	15.94
5/SPB6000GL	5	SPB	6000	236.22	7.75	17.08
5/SPB6300GL	5	SPB	6300	248.03	8.13	17.93
5/SPB6700GL	5	SPB	6700	263.78	8.65	19.07
5/SPB7100GL	5	SPB	7100	279.53	9.17	20.21
5/SPB7500GL	5	SPB	7500	295.28	9.68	21.35
5/SPB8000GL	5	SPB	8000	314.96	10.33	22.77
16/SPB2000GL	16	SPB	2000	78.74	8.26	18.22
16/SPB2120GL	16	SPB	2120	83.46	8.76	19.31
16/SPB2240GL	16	SPB	2240	88.19	9.25	20.40
16/SPB2360GL	16	SPB	2360	92.91	9.75	21.49
16/SPB2500GL	16	SPB	2500	98.43	10.33	22.77
16/SPB2650GL	16	SPB	2650	104.33	10.95	24.14
24/SPB2800GL	24	SPB	2800	110.24	17.35	38.25
24/SPB3000GL	24	SPB	3000	118.11	18.59	40.99
24/SPB3150GL	24	SPB	3150	124.02	19.52	43.04
24/SPB3350GL	24	SPB	3350	131.89	20.76	45.77
24/SPB3550GL	24	SPB	3550	139.76	22.00	48.50
24/SPB3750GL	24	SPB	3750	147.64	23.24	51.23
24/SPB4000GL	24	SPB	4000	157.48	24.79	54.65
24/SPB4250GL	24	SPB	4250	167.32	26.34	58.06
24/SPB4500GL	24	SPB	4500	177.17	27.89	61.48
24/SPB4750GL	24	SPB	4750	187.01	29.44	64.89
24/SPB5000GL	24	SPB	5000	196.85	30.98	68.31
24/SPB5300GL	24	SPB	5300	208.66	32.84	72.41
24/SPB5600GL	24	SPB	5600	220.47	34.70	76.51
24/SPB6000GL	24	SPB	6000	236.22	37.18	81.97
24/SPB6300GL	24	SPB	6300	248.03	39.04	86.07
24/SPB6700GL	24	SPB	6700	263.78	41.52	91.54
24/SPB7100GL	24	SPB	7100	279.53	44.00	97.00
24/SPB7500GL	24	SPB	7500	295.28	46.48	102.46
24/SPB8000GL	24	SPB	8000	314.96	49.58	109.30
2/SPC3000GL	2	SPC	3000	118.11	3.41	7.51



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/SPC3150GL	2	SPC	3150	124.02	3.58	7.89
2/SPC3350GL	2	SPC	3350	131.89	3.81	8.39
2/SPC3550GL	2	SPC	3550	139.76	4.03	8.89
2/SPC3750GL	2	SPC	3750	147.64	4.26	9.39
2/SPC4000GL	2	SPC	4000	157.48	4.54	10.02
2/SPC4250GL	2	SPC	4250	167.32	4.83	10.64
2/SPC4500GL	2	SPC	4500	177.17	5.11	11.27
2/SPC4750GL	2	SPC	4750	187.01	5.40	11.90
2/SPC5000GL	2	SPC	5000	196.85	5.68	12.52
2/SPC5300GL	2	SPC	5300	208.66	6.02	13.27
2/SPC5600GL	2	SPC	5600	220.47	6.36	14.02
2/SPC6000GL	2	SPC	6000	236.22	6.82	15.03
2/SPC6300GL	2	SPC	6300	248.03	7.16	15.78
2/SPC6700GL	2	SPC	6700	263.78	7.61	16.78
2/SPC7100GL	2	SPC	7100	279.53	8.07	17.78
2/SPC7500GL	2	SPC	7500	295.28	8.52	18.78
2/SPC8000GL	2	SPC	8000	314.96	9.09	20.04
2/SPC8500GL	2	SPC	8500	334.65	9.66	21.29
2/SPC9000GL	2	SPC	9000	354.33	10.22	22.54
2/SPC9500GL	2	SPC	9500	374.02	10.79	23.79
2/SPC10000GL	2	SPC	10000	393.70	11.36	25.04
2/SPC10600GL	2	SPC	10600	417.32	12.04	26.55
2/SPC11200GL	2	SPC	11200	440.94	12.72	28.05
2/SPC11800GL	2	SPC	11800	464.57	13.40	29.55
2/SPC12500GL	2	SPC	12500	492.13	14.20	31.31
3/SPC3000GL	3	SPC	3000	118.11	5.11	11.27
3/SPC3150GL	3	SPC	3150	124.02	5.37	11.83
3/SPC3350GL	3	SPC	3350	131.89	5.71	12.58
3/SPC3550GL	3	SPC	3550	139.76	6.05	13.34
3/SPC3750GL	3	SPC	3750	147.64	6.39	14.09
3/SPC4000GL	3	SPC	4000	157.48	6.82	15.03
3/SPC4250GL	3	SPC	4250	167.32	7.24	15.97
3/SPC4500GL	3	SPC	4500	177.17	7.67	16.90
3/SPC4750GL	3	SPC	4750	187.01	8.09	17.84



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/SPC5000GL	3	SPC	5000	196.85	8.52	18.78
3/SPC5300GL	3	SPC	5300	208.66	9.03	19.91
3/SPC5600GL	3	SPC	5600	220.47	9.54	21.04
3/SPC6000GL	3	SPC	6000	236.22	10.22	22.54
3/SPC6300GL	3	SPC	6300	248.03	10.74	23.67
3/SPC6700GL	3	SPC	6700	263.78	11.42	25.17
3/SPC7100GL	3	SPC	7100	279.53	12.10	26.67
3/SPC7500GL	3	SPC	7500	295.28	12.78	28.17
3/SPC8000GL	3	SPC	8000	314.96	13.63	30.05
3/SPC8500GL	3	SPC	8500	334.65	14.48	31.93
3/SPC9000GL	3	SPC	9000	354.33	15.34	33.81
3/SPC9500GL	3	SPC	9500	374.02	16.19	35.69
3/SPC10000GL	3	SPC	10000	393.70	17.04	37.57
3/SPC10600GL	3	SPC	10600	417.32	18.06	39.82
3/SPC11200GL	3	SPC	11200	440.94	19.08	42.07
3/SPC11800GL	3	SPC	11800	464.57	20.11	44.33
3/SPC12500GL	3	SPC	12500	492.13	21.30	46.96
4/SPC3000GL	4	SPC	3000	118.11	6.82	15.03
4/SPC3150GL	4	SPC	3150	124.02	7.16	15.78
4/SPC3350GL	4	SPC	3350	131.89	7.61	16.78
4/SPC3550GL	4	SPC	3550	139.76	8.07	17.78
4/SPC3750GL	4	SPC	3750	147.64	8.52	18.78
4/SPC4000GL	4	SPC	4000	157.48	9.09	20.04
4/SPC4250GL	4	SPC	4250	167.32	9.66	21.29
4/SPC4500GL	4	SPC	4500	177.17	10.22	22.54
4/SPC4750GL	4	SPC	4750	187.01	10.79	23.79
4/SPC5000GL	4	SPC	5000	196.85	11.36	25.04
4/SPC5300GL	4	SPC	5300	208.66	12.04	26.55
4/SPC5600GL	4	SPC	5600	220.47	12.72	28.05
4/SPC6000GL	4	SPC	6000	236.22	13.63	30.05
4/SPC6300GL	4	SPC	6300	248.03	14.31	31.56
4/SPC6700GL	4	SPC	6700	263.78	15.22	33.56
4/SPC7100GL	4	SPC	7100	279.53	16.13	35.56
4/SPC7500GL	4	SPC	7500	295.28	17.04	37.57



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/SPC8000GL	4	SPC	8000	314.96	18.18	40.07
4/SPC8500GL	4	SPC	8500	334.65	19.31	42.58
4/SPC9000GL	4	SPC	9000	354.33	20.45	45.08
4/SPC9500GL	4	SPC	9500	374.02	21.58	47.58
4/SPC10000GL	4	SPC	10000	393.70	22.72	50.09
4/SPC10600GL	4	SPC	10600	417.32	24.08	53.09
4/SPC11200GL	4	SPC	11200	440.94	25.45	56.10
4/SPC11800GL	4	SPC	11800	464.57	26.81	59.10
4/SPC12500GL	4	SPC	12500	492.13	28.40	62.61
5/SPC3000GL	5	SPC	3000	118.11	8.52	18.78
5/SPC3150GL	5	SPC	3150	124.02	8.95	19.72
5/SPC3350GL	5	SPC	3350	131.89	9.51	20.97
5/SPC3550GL	5	SPC	3550	139.76	10.08	22.23
5/SPC3750GL	5	SPC	3750	147.64	10.65	23.48
5/SPC4000GL	5	SPC	4000	157.48	11.36	25.04
5/SPC4250GL	5	SPC	4250	167.32	12.07	26.61
5/SPC4500GL	5	SPC	4500	177.17	12.78	28.17
5/SPC4750GL	5	SPC	4750	187.01	13.49	29.74
5/SPC5000GL	5	SPC	5000	196.85	14.20	31.31
5/SPC5300GL	5	SPC	5300	208.66	15.05	33.18
5/SPC5600GL	5	SPC	5600	220.47	15.90	35.06
5/SPC6000GL	5	SPC	6000	236.22	17.04	37.57
5/SPC6300GL	5	SPC	6300	248.03	17.89	39.44
5/SPC6700GL	5	SPC	6700	263.78	19.03	41.95
5/SPC7100GL	5	SPC	7100	279.53	20.16	44.45
5/SPC7500GL	5	SPC	7500	295.28	21.30	46.96
5/SPC8000GL	5	SPC	8000	314.96	22.72	50.09
5/SPC8500GL	5	SPC	8500	334.65	24.14	53.22
5/SPC9000GL	5	SPC	9000	354.33	25.56	56.35
5/SPC9500GL	5	SPC	9500	374.02	26.98	59.48
5/SPC10000GL	5	SPC	10000	393.70	28.40	62.61
5/SPC10600GL	5	SPC	10600	417.32	30.10	66.37
5/SPC11200GL	5	SPC	11200	440.94	31.81	70.12
5/SPC11800GL	5	SPC	11800	464.57	33.51	73.88



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032


All number of ribs between 2 and the max number in the table below are available

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
5/SPC12500GL	5	SPC	12500	492.13	35.50	78.26
18/SPC8000GL	18	SPC	8000	314.96	81.79	180.32
18/SPC8500GL	18	SPC	8500	334.65	86.90	191.59
18/SPC9000GL	18	SPC	9000	354.33	92.02	202.86
18/SPC9500GL	18	SPC	9500	374.02	97.13	214.13
18/SPC10000GL	18	SPC	10000	393.70	102.24	225.40
18/SPC10600GL	18	SPC	10600	417.32	108.37	238.92
18/SPC11200GL	18	SPC	11200	440.94	114.51	252.45
18/SPC11800GL	18	SPC	11800	464.57	120.64	265.97
18/SPC12500GL	18	SPC	12500	492.13	127.80	281.75
22/SPC3000GL	22	SPC	3000	118.11	37.49	82.65
22/SPC3150GL	22	SPC	3150	124.02	39.36	86.78
22/SPC3350GL	22	SPC	3350	131.89	41.86	92.29
22/SPC3550GL	22	SPC	3550	139.76	44.36	97.80
22/SPC3750GL	22	SPC	3750	147.64	46.86	103.31
22/SPC4000GL	22	SPC	4000	157.48	49.98	110.19
22/SPC4250GL	22	SPC	4250	167.32	53.11	117.08
22/SPC4500GL	22	SPC	4500	177.17	56.23	123.97
22/SPC4750GL	22	SPC	4750	187.01	59.36	130.86
22/SPC5000GL	22	SPC	5000	196.85	62.48	137.74
22/SPC5300GL	22	SPC	5300	208.66	66.23	146.01
22/SPC5600GL	22	SPC	5600	220.47	69.98	154.27
22/SPC6000GL	22	SPC	6000	236.22	74.98	165.29
22/SPC6300GL	22	SPC	6300	248.03	78.72	173.56
22/SPC6700GL	22	SPC	6700	263.78	83.72	184.58
22/SPC7100GL	22	SPC	7100	279.53	88.72	195.60
22/SPC7500GL	22	SPC	7500	295.28	93.72	206.62



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Classical



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
BX	17	13	0.182
CX	22	16	0.317

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
BX	21/32	1/2	0.010
CX	7/8	5/8	0.018

V-Belt Raw Edge

Part Number Description: **2/BX100GL**

2/: Number of ribs

BX: Profile

100: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, Rubber Impregnated

- Abrasion resistance
- Prevents vibrations and belt turn-over

Tension Cords: High Modulus Polyester

- Superior dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads
- Improved durability
- Reduced maintenance

Cogs Profile

- Improved bending fatigue
- Extra flexibility for smaller pulleys
- Cooling effects

Compression Rubber: Fiber Loaded EPDM Rubber Blend

- Good abrasion and ozone resistance
- Superior heat resistance
- High coefficient of friction (increased power capacity vs. wrapped belt)
- Temperature range: -40°F (-40°C) to 302°F (150°C)
- Static conductive ISO1813

Markets and Applications:


Designed for high horsepower and shock load applications, these industrial banded belts are primarily employed on applications where multiple belts have the tendency to vibrate, turn over or come off pulleys when subjected to fluctuating load tensions and high horsepower.

The Dayco GOLD LABEL industrial banded belt is available in both wrapped molded construction and raw edge versions and provides the same oil and heat resistant characteristics as the Dayco GOLD LABEL single belts with the addition of a fabric rubber top band for multiple belt stability.



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Classical - Size List



V-Belt Raw Edge

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
BX	17	13	0.182
CX	22	16	0.317


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
BX	21/32	1/2	0.010
CX	7/8	5/8	0.018

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/BX42GL	2	BX	1067	42.00	0.39	0.86
2/BX46GL	2	BX	1168	46.00	0.43	0.94
2/BX51GL	2	BX	1295	51.00	0.47	1.04
2/BX53GL	2	BX	1346	53.00	0.49	1.08
2/BX55GL	2	BX	1397	55.00	0.51	1.12
2/BX56GL	2	BX	1422	56.00	0.52	1.14
2/BX58GL	2	BX	1473	58.00	0.54	1.18
2/BX60GL	2	BX	1524	60.00	0.55	1.22
2/BX62GL	2	BX	1575	62.00	0.57	1.26
2/BX63GL	2	BX	1600	63.00	0.58	1.28
2/BX64GL	2	BX	1626	64.00	0.59	1.31
2/BX65GL	2	BX	1651	65.00	0.60	1.33
2/BX66GL	2	BX	1676	66.00	0.61	1.35
2/BX67GL	2	BX	1702	67.00	0.62	1.37
2/BX68GL	2	BX	1727	68.00	0.63	1.39
2/BX70GL	2	BX	1778	70.00	0.65	1.43
2/BX71GL	2	BX	1803	71.00	0.66	1.45
2/BX74GL	2	BX	1880	74.00	0.68	1.51
2/BX75GL	2	BX	1905	75.00	0.69	1.53
2/BX77GL	2	BX	1956	77.00	0.71	1.57
2/BX79GL	2	BX	2007	79.00	0.73	1.61
2/BX81GL	2	BX	2057	81.00	0.75	1.65
2/BX83GL	2	BX	2108	83.00	0.77	1.69
2/BX84GL	2	BX	2134	84.00	0.78	1.71
2/BX85GL	2	BX	2159	85.00	0.79	1.73
2/BX87GL	2	BX	2210	87.00	0.80	1.77
2/BX90GL	2	BX	2286	90.00	0.83	1.84
2/BX93GL	2	BX	2362	93.00	0.86	1.90
2/BX96GL	2	BX	2438	96.00	0.89	1.96
2/BX97GL	2	BX	2464	97.00	0.90	1.98
2/BX100GL	2	BX	2540	100.00	0.92	2.04
2/BX103GL	2	BX	2616	103.00	0.95	2.10



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Classical - Size List



V-Belt Raw Edge

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
BX	17	13	0.182
CX	22	16	0.317


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
BX	21/32	1/2	0.010
CX	7/8	5/8	0.018

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/BX105GL	2	BX	2667	105.00	0.97	2.14
2/BX112GL	2	BX	2845	112.00	1.04	2.28
3/BX42GL	3	BX	1067	42.00	0.58	1.28
3/BX46GL	3	BX	1168	46.00	0.64	1.41
3/BX51GL	3	BX	1295	51.00	0.71	1.56
3/BX53GL	3	BX	1346	53.00	0.74	1.62
3/BX55GL	3	BX	1397	55.00	0.76	1.68
3/BX56GL	3	BX	1422	56.00	0.78	1.71
3/BX58GL	3	BX	1473	58.00	0.80	1.77
3/BX60GL	3	BX	1524	60.00	0.83	1.84
3/BX62GL	3	BX	1575	62.00	0.86	1.90
3/BX63GL	3	BX	1600	63.00	0.87	1.93
3/BX64GL	3	BX	1626	64.00	0.89	1.96
3/BX65GL	3	BX	1651	65.00	0.90	1.99
3/BX66GL	3	BX	1676	66.00	0.92	2.02
3/BX67GL	3	BX	1702	67.00	0.93	2.05
3/BX68GL	3	BX	1727	68.00	0.94	2.08
3/BX70GL	3	BX	1778	70.00	0.97	2.14
3/BX71GL	3	BX	1803	71.00	0.99	2.17
3/BX74GL	3	BX	1880	74.00	1.03	2.26
3/BX75GL	3	BX	1905	75.00	1.04	2.29
3/BX77GL	3	BX	1956	77.00	1.07	2.36
3/BX79GL	3	BX	2007	79.00	1.10	2.42
3/BX81GL	3	BX	2057	81.00	1.12	2.48
3/BX83GL	3	BX	2108	83.00	1.15	2.54
3/BX84GL	3	BX	2134	84.00	1.17	2.57
3/BX85GL	3	BX	2159	85.00	1.18	2.60
3/BX87GL	3	BX	2210	87.00	1.21	2.66
3/BX90GL	3	BX	2286	90.00	1.25	2.75
3/BX93GL	3	BX	2362	93.00	1.29	2.84
3/BX96GL	3	BX	2438	96.00	1.33	2.94
3/BX97GL	3	BX	2464	97.00	1.35	2.97



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Classical - Size List



V-Belt Raw Edge

GOLD LABEL®

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
BX	17	13	0.182
CX	22	16	0.317


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
BX	21/32	1/2	0.010
CX	7/8	5/8	0.018

DAYCO Part #	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/BX100GL	3	BX	2540	100.00	1.39	3.06
3/BX103GL	3	BX	2616	103.00	1.43	3.15
3/BX105GL	3	BX	2667	105.00	1.46	3.21
3/BX112GL	3	BX	2845	112.00	1.55	3.43
2/CX75GL	2	CX	1905	75.00	1.21	2.67
2/CX81GL	2	CX	2057	81.00	1.31	2.88
2/CX85GL	2	CX	2159	85.00	1.37	3.02
2/CX90GL	2	CX	2286	90.00	1.45	3.20
2/CX96GL	2	CX	2438	96.00	1.55	3.41
2/CX100GL	2	CX	2540	100.00	1.61	3.56
2/CX105GL	2	CX	2667	105.00	1.69	3.73
2/CX112GL	2	CX	2845	112.00	1.81	3.98



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Narrow



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

V-Belt Raw Edge

Part Number Description: **2/3VX800GL**

2/: Number of ribs

3VX: Profile

800: External Length (tenths of an inch)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, Rubber Impregnated

- Abrasion resistance
- Prevents vibrations and belt turn-over

Tension Cords: High Modulus Polyester

- Superior dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads
- Improved durability
- Reduced maintenance

Cogs Profile

- Improved bending fatigue
- Extra flexibility for smaller pulleys
- Cooling effects

Compression Rubber: Fiber Loaded EPDM Rubber Blend

- Good abrasion and ozone resistance
- Superior heat resistance
- High coefficient of friction (increased power capacity vs. wrapped belt)
- Temperature range: -40°F (-40°C) to 302°F (150°C)
- Static conductive ISO1813

Markets and Applications:


Designed for high horsepower and shock load applications, these industrial banded belts are primarily employed on applications where multiple belts have the tendency to vibrate, turn over or come off pulleys when subjected to fluctuating load tensions and high horsepower.

The Dayco GOLD LABEL® industrial banded belt is available in both wrapped molded construction and raw edge versions and provides the same oil and heat resistant characteristics as the Dayco GOLD LABEL single belts with the addition of a fabric rubber top band for multiple belt stability.



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/3VX250GL	2	3VX	635	25.00	0.10	0.22
2/3VX265GL	2	3VX	660	26.00	0.11	0.23
2/3VX280GL	2	3VX	711	28.00	0.11	0.25
2/3VX300GL	2	3VX	762	30.00	0.12	0.27
2/3VX315GL	2	3VX	787	31.00	0.13	0.28
2/3VX335GL	2	3VX	838	33.00	0.13	0.30
2/3VX355GL	2	3VX	889	35.00	0.14	0.31
2/3VX375GL	2	3VX	940	37.00	0.15	0.33
2/3VX400GL	2	3VX	1016	40.00	0.16	0.36
2/3VX425GL	2	3VX	1067	42.00	0.17	0.38
2/3VX450GL	2	3VX	1143	45.00	0.18	0.40
2/3VX475GL	2	3VX	1194	47.00	0.19	0.42
2/3VX500GL	2	3VX	1270	50.00	0.20	0.45
2/3VX530GL	2	3VX	1346	53.00	0.22	0.48
2/3VX560GL	2	3VX	1422	56.00	0.23	0.50
2/3VX600GL	2	3VX	1524	60.00	0.24	0.54
2/3VX630GL	2	3VX	1600	63.00	0.26	0.56
2/3VX670GL	2	3VX	1702	67.00	0.27	0.60
2/3VX710GL	2	3VX	1803	71.00	0.29	0.64
2/3VX750GL	2	3VX	1905	75.00	0.30	0.67
2/3VX800GL	2	3VX	2032	80.00	0.33	0.72
2/3VX820GL	2	3VX	2083	82.00	0.33	0.74
2/3VX850GL	2	3VX	2159	85.00	0.35	0.76
2/3VX900GL	2	3VX	2286	90.00	0.37	0.81
2/3VX950GL	2	3VX	2413	95.00	0.39	0.85
2/3VX1000GL	2	3VX	2540	100.00	0.41	0.90
2/3VX1060GL	2	3VX	2692	106.00	0.43	0.95
2/3VX1120GL	2	3VX	2845	112.00	0.46	1.00
3/3VX250GL	3	3VX	635	25.00	0.15	0.34
3/3VX265GL	3	3VX	660	26.00	0.16	0.35
3/3VX280GL	3	3VX	711	28.00	0.17	0.38
3/3VX300GL	3	3VX	762	30.00	0.18	0.40
3/3VX315GL	3	3VX	787	31.00	0.19	0.42
3/3VX335GL	3	3VX	838	33.00	0.20	0.44



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
3/3VX355GL	3	3VX	889	35.00	0.21	0.47
3/3VX375GL	3	3VX	940	37.00	0.23	0.50
3/3VX400GL	3	3VX	1016	40.00	0.24	0.54
3/3VX425GL	3	3VX	1067	42.00	0.26	0.56
3/3VX450GL	3	3VX	1143	45.00	0.27	0.61
3/3VX475GL	3	3VX	1194	47.00	0.29	0.63
3/3VX500GL	3	3VX	1270	50.00	0.30	0.67
3/3VX530GL	3	3VX	1346	53.00	0.32	0.71
3/3VX560GL	3	3VX	1422	56.00	0.34	0.75
3/3VX600GL	3	3VX	1524	60.00	0.37	0.81
3/3VX630GL	3	3VX	1600	63.00	0.38	0.85
3/3VX670GL	3	3VX	1702	67.00	0.41	0.90
3/3VX710GL	3	3VX	1803	71.00	0.43	0.95
3/3VX750GL	3	3VX	1905	75.00	0.46	1.01
3/3VX800GL	3	3VX	2032	80.00	0.49	1.08
3/3VX820GL	3	3VX	2083	82.00	0.50	1.10
3/3VX850GL	3	3VX	2159	85.00	0.52	1.14
3/3VX900GL	3	3VX	2286	90.00	0.55	1.21
3/3VX950GL	3	3VX	2413	95.00	0.58	1.28
3/3VX1000GL	3	3VX	2540	100.00	0.61	1.34
3/3VX1060GL	3	3VX	2692	106.00	0.65	1.43
3/3VX1120GL	3	3VX	2845	112.00	0.68	1.51
4/3VX250GL	4	3VX	635	25.00	0.20	0.45
4/3VX265GL	4	3VX	660	26.00	0.21	0.47
4/3VX280GL	4	3VX	711	28.00	0.23	0.50
4/3VX300GL	4	3VX	762	30.00	0.24	0.54
4/3VX315GL	4	3VX	787	31.00	0.25	0.56
4/3VX335GL	4	3VX	838	33.00	0.27	0.59
4/3VX355GL	4	3VX	889	35.00	0.28	0.63
4/3VX375GL	4	3VX	940	37.00	0.30	0.66
4/3VX400GL	4	3VX	1016	40.00	0.33	0.72
4/3VX425GL	4	3VX	1067	42.00	0.34	0.75
4/3VX450GL	4	3VX	1143	45.00	0.37	0.81
4/3VX475GL	4	3VX	1194	47.00	0.38	0.84



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
4/3VX500GL	4	3VX	1270	50.00	0.41	0.90
4/3VX530GL	4	3VX	1346	53.00	0.43	0.95
4/3VX560GL	4	3VX	1422	56.00	0.46	1.00
4/3VX600GL	4	3VX	1524	60.00	0.49	1.08
4/3VX630GL	4	3VX	1600	63.00	0.51	1.13
4/3VX670GL	4	3VX	1702	67.00	0.54	1.20
4/3VX710GL	4	3VX	1803	71.00	0.58	1.27
4/3VX750GL	4	3VX	1905	75.00	0.61	1.34
4/3VX800GL	4	3VX	2032	80.00	0.65	1.43
4/3VX820GL	4	3VX	2083	82.00	0.67	1.47
4/3VX850GL	4	3VX	2159	85.00	0.69	1.52
4/3VX900GL	4	3VX	2286	90.00	0.73	1.61
4/3VX950GL	4	3VX	2413	95.00	0.77	1.70
4/3VX1000GL	4	3VX	2540	100.00	0.81	1.79
4/3VX1060GL	4	3VX	2692	106.00	0.86	1.90
4/3VX1120GL	4	3VX	2845	112.00	0.91	2.01
5/3VX250GL	5	3VX	635	25.00	0.25	0.56
5/3VX265GL	5	3VX	660	26.00	0.26	0.58
5/3VX280GL	5	3VX	711	28.00	0.28	0.63
5/3VX300GL	5	3VX	762	30.00	0.30	0.67
5/3VX315GL	5	3VX	787	31.00	0.32	0.69
5/3VX335GL	5	3VX	838	33.00	0.34	0.74
5/3VX355GL	5	3VX	889	35.00	0.36	0.78
5/3VX375GL	5	3VX	940	37.00	0.38	0.83
5/3VX400GL	5	3VX	1016	40.00	0.41	0.90
5/3VX425GL	5	3VX	1067	42.00	0.43	0.94
5/3VX450GL	5	3VX	1143	45.00	0.46	1.01
5/3VX475GL	5	3VX	1194	47.00	0.48	1.05
5/3VX500GL	5	3VX	1270	50.00	0.51	1.12
5/3VX530GL	5	3VX	1346	53.00	0.54	1.19
5/3VX560GL	5	3VX	1422	56.00	0.57	1.25
5/3VX600GL	5	3VX	1524	60.00	0.61	1.34
5/3VX630GL	5	3VX	1600	63.00	0.64	1.41
5/3VX670GL	5	3VX	1702	67.00	0.68	1.50



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
5/3VX710GL	5	3VX	1803	71.00	0.72	1.59
5/3VX750GL	5	3VX	1905	75.00	0.76	1.68
5/3VX800GL	5	3VX	2032	80.00	0.81	1.79
5/3VX820GL	5	3VX	2083	82.00	0.83	1.84
5/3VX850GL	5	3VX	2159	85.00	0.86	1.90
5/3VX900GL	5	3VX	2286	90.00	0.91	2.02
5/3VX950GL	5	3VX	2413	95.00	0.97	2.13
5/3VX1000GL	5	3VX	2540	100.00	1.02	2.24
5/3VX1060GL	5	3VX	2692	106.00	1.08	2.38
5/3VX1120GL	5	3VX	2845	112.00	1.14	2.51
6/3VX250GL	6	3VX	635	25.00	0.30	0.67
6/3VX265GL	6	3VX	660	26.00	0.32	0.70
6/3VX280GL	6	3VX	711	28.00	0.34	0.75
6/3VX300GL	6	3VX	762	30.00	0.37	0.81
6/3VX315GL	6	3VX	787	31.00	0.38	0.83
6/3VX335GL	6	3VX	838	33.00	0.40	0.89
6/3VX355GL	6	3VX	889	35.00	0.43	0.94
6/3VX375GL	6	3VX	940	37.00	0.45	0.99
6/3VX400GL	6	3VX	1016	40.00	0.49	1.08
6/3VX425GL	6	3VX	1067	42.00	0.51	1.13
6/3VX450GL	6	3VX	1143	45.00	0.55	1.21
6/3VX475GL	6	3VX	1194	47.00	0.57	1.26
6/3VX500GL	6	3VX	1270	50.00	0.61	1.34
6/3VX530GL	6	3VX	1346	53.00	0.65	1.43
6/3VX560GL	6	3VX	1422	56.00	0.68	1.51
6/3VX600GL	6	3VX	1524	60.00	0.73	1.61
6/3VX630GL	6	3VX	1600	63.00	0.77	1.69
6/3VX670GL	6	3VX	1702	67.00	0.82	1.80
6/3VX710GL	6	3VX	1803	71.00	0.87	1.91
6/3VX750GL	6	3VX	1905	75.00	0.91	2.02
6/3VX800GL	6	3VX	2032	80.00	0.98	2.15
6/3VX820GL	6	3VX	2083	82.00	1.00	2.21
6/3VX850GL	6	3VX	2159	85.00	1.04	2.29
6/3VX900GL	6	3VX	2286	90.00	1.10	2.42



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part #	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
6/3VX950GL	6	3VX	2413	95.00	1.16	2.55
6/3VX1000GL	6	3VX	2540	100.00	1.22	2.69
6/3VX1060GL	6	3VX	2692	106.00	1.29	2.85
6/3VX1120GL	6	3VX	2845	112.00	1.37	3.01
2/5VX500GL	2	5VX	1270	50.00	0.58	1.27
2/5VX530GL	2	5VX	1346	53.00	0.61	1.35
2/5VX560GL	2	5VX	1422	56.00	0.65	1.42
2/5VX600GL	2	5VX	1524	60.00	0.69	1.52
2/5VX630GL	2	5VX	1600	63.00	0.73	1.60
2/5VX670GL	2	5VX	1702	67.00	0.77	1.70
2/5VX710GL	2	5VX	1803	71.00	0.82	1.80
2/5VX750GL	2	5VX	1905	75.00	0.86	1.90
2/5VX800GL	2	5VX	2032	80.00	0.92	2.03
2/5VX850GL	2	5VX	2159	85.00	0.98	2.16
2/5VX900GL	2	5VX	2286	90.00	1.04	2.29
2/5VX950GL	2	5VX	2413	95.00	1.09	2.41
2/5VX1000GL	2	5VX	2540	100.00	1.15	2.54
2/5VX1060GL	2	5VX	2692	106.00	1.22	2.69
2/5VX1120GL	2	5VX	2845	112.00	1.29	2.84
3/5VX500GL	3	5VX	1270	50.00	0.86	1.90
3/5VX530GL	3	5VX	1346	53.00	0.92	2.02
3/5VX560GL	3	5VX	1422	56.00	0.97	2.13
3/5VX600GL	3	5VX	1524	60.00	1.04	2.29
3/5VX630GL	3	5VX	1600	63.00	1.09	2.40
3/5VX670GL	3	5VX	1702	67.00	1.16	2.55
3/5VX710GL	3	5VX	1803	71.00	1.23	2.70
3/5VX750GL	3	5VX	1905	75.00	1.30	2.86
3/5VX800GL	3	5VX	2032	80.00	1.38	3.05
3/5VX850GL	3	5VX	2159	85.00	1.47	3.24
3/5VX900GL	3	5VX	2286	90.00	1.56	3.43
3/5VX950GL	3	5VX	2413	95.00	1.64	3.62
3/5VX1000GL	3	5VX	2540	100.00	1.73	3.81
3/5VX1060GL	3	5VX	2692	106.00	1.83	4.04
3/5VX1120GL	3	5VX	2845	112.00	1.94	4.27



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

V-Belt Raw Edge

Part Number Description: **2/XPA1250GL**

2/: Number of ribs

XPA: Profile

1250: Datum Length (mm)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, Rubber Impregnated

- Abrasion resistance
- Prevents vibrations and belt turn-over

Tension Cords: High Modulus Polyester

- Superior dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads
- Improved durability
- Reduced maintenance

Cogs Profile

- Improved bending fatigue
- Extra flexibility for smaller pulleys
- Cooling effects

Compression Rubber: Fiber Loaded EPDM Rubber Blend

- Good abrasion and ozone resistance
- Superior heat resistance
- High coefficient of friction (increased power capacity vs. wrapped belt)
- Temperature Range: - Temperature range: -40°F (-40°C) to 302°F (150°C)
- Static conductive ISO1813

Markets and Applications:


Designed for high horsepower and shock load applications, these industrial banded belts are primarily employed on applications where multiple belts have the tendency to vibrate, turn over or come off pulleys when subjected to fluctuating load tensions and high horsepower.

The Dayco GOLD LABEL industrial banded belt is available in both wrapped molded construction and raw edge versions and provides the same oil and heat resistant characteristics as the Dayco GOLD LABEL single belts with the addition of a fabric rubber top band for multiple belt stability.



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/XPZ800GL	2	XPZ	800	31.50	0.29	0.13
2/XPZ850GL	2	XPZ	850	33.46	0.31	0.14
2/XPZ900GL	2	XPZ	900	35.43	0.33	0.15
2/XPZ950GL	2	XPZ	950	37.40	0.34	0.16
2/XPZ1000GL	2	XPZ	1000	39.37	0.36	0.16
2/XPZ1030GL	2	XPZ	1030	40.55	0.37	0.17
2/XPZ1060GL	2	XPZ	1060	41.73	0.38	0.17
2/XPZ1090GL	2	XPZ	1090	42.91	0.39	0.18
2/XPZ1120GL	2	XPZ	1120	44.09	0.41	0.18
2/XPZ1150GL	2	XPZ	1150	45.28	0.42	0.19
2/XPZ1180GL	2	XPZ	1180	46.46	0.43	0.19
2/XPZ1212GL	2	XPZ	1212	47.72	0.44	0.20
2/XPZ1250GL	2	XPZ	1250	49.21	0.45	0.21
2/XPZ1270GL	2	XPZ	1270	50.00	0.46	0.21
2/XPZ1320GL	2	XPZ	1320	51.97	0.48	0.22
2/XPZ1340GL	2	XPZ	1340	52.76	0.49	0.22
2/XPZ1362GL	2	XPZ	1362	53.62	0.49	0.22
2/XPZ1400GL	2	XPZ	1400	55.12	0.51	0.23
2/XPZ1420GL	2	XPZ	1420	55.91	0.51	0.23
2/XPZ1450GL	2	XPZ	1450	57.09	0.53	0.24
2/XPZ1487GL	2	XPZ	1487	58.54	0.54	0.24
2/XPZ1500GL	2	XPZ	1500	59.06	0.54	0.25
2/XPZ1550GL	2	XPZ	1550	61.02	0.56	0.25
2/XPZ1600GL	2	XPZ	1600	62.99	0.58	0.26
2/XPZ1650GL	2	XPZ	1650	64.96	0.60	0.27
2/XPZ1700GL	2	XPZ	1700	66.93	0.62	0.28
2/XPZ1750GL	2	XPZ	1750	68.90	0.63	0.29
2/XPZ1800GL	2	XPZ	1800	70.87	0.65	0.30
2/XPZ1850GL	2	XPZ	1850	72.83	0.67	0.30
2/XPZ1900GL	2	XPZ	1900	74.80	0.69	0.31
2/XPZ1950GL	2	XPZ	1950	76.77	0.71	0.32
2/XPZ2000GL	2	XPZ	2000	78.74	0.72	0.33
2/XPZ2030GL	2	XPZ	2030	79.92	0.74	0.33
2/XPZ2120GL	2	XPZ	2120	83.46	0.77	0.35



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/XPZ2160GL	2	XPZ	2160	85.04	0.78	0.35
2/XPZ2240GL	2	XPZ	2240	88.19	0.81	0.37
2/XPZ2360GL	2	XPZ	2360	92.91	0.85	0.39
2/XPZ2500GL	2	XPZ	2500	98.43	0.91	0.41
2/XPZ2650GL	2	XPZ	2650	104.33	0.96	0.44
2/XPZ2800GL	2	XPZ	2800	110.24	1.01	0.46
3/XPZ800GL	3	XPZ	800	31.50	0.43	0.20
3/XPZ850GL	3	XPZ	850	33.46	0.46	0.21
3/XPZ900GL	3	XPZ	900	35.43	0.49	0.22
3/XPZ950GL	3	XPZ	950	37.40	0.52	0.23
3/XPZ1000GL	3	XPZ	1000	39.37	0.54	0.25
3/XPZ1030GL	3	XPZ	1030	40.55	0.56	0.25
3/XPZ1060GL	3	XPZ	1060	41.73	0.58	0.26
3/XPZ1090GL	3	XPZ	1090	42.91	0.59	0.27
3/XPZ1120GL	3	XPZ	1120	44.09	0.61	0.28
3/XPZ1150GL	3	XPZ	1150	45.28	0.62	0.28
3/XPZ1180GL	3	XPZ	1180	46.46	0.64	0.29
3/XPZ1212GL	3	XPZ	1212	47.72	0.66	0.30
3/XPZ1250GL	3	XPZ	1250	49.21	0.68	0.31
3/XPZ1270GL	3	XPZ	1270	50.00	0.69	0.31
3/XPZ1320GL	3	XPZ	1320	51.97	0.72	0.33
3/XPZ1340GL	3	XPZ	1340	52.76	0.73	0.33
3/XPZ1362GL	3	XPZ	1362	53.62	0.74	0.34
3/XPZ1400GL	3	XPZ	1400	55.12	0.76	0.35
3/XPZ1420GL	3	XPZ	1420	55.91	0.77	0.35
3/XPZ1450GL	3	XPZ	1450	57.09	0.79	0.36
3/XPZ1487GL	3	XPZ	1487	58.54	0.81	0.37
3/XPZ1500GL	3	XPZ	1500	59.06	0.81	0.37
3/XPZ1550GL	3	XPZ	1550	61.02	0.84	0.38
3/XPZ1600GL	3	XPZ	1600	62.99	0.87	0.39
3/XPZ1650GL	3	XPZ	1650	64.96	0.90	0.41
3/XPZ1700GL	3	XPZ	1700	66.93	0.92	0.42
3/XPZ1750GL	3	XPZ	1750	68.90	0.95	0.43
3/XPZ1800GL	3	XPZ	1800	70.87	0.98	0.44



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/XPZ1850GL	3	XPZ	1850	72.83	1.01	0.46
3/XPZ1900GL	3	XPZ	1900	74.80	1.03	0.47
3/XPZ1950GL	3	XPZ	1950	76.77	1.06	0.48
3/XPZ2000GL	3	XPZ	2000	78.74	1.09	0.49
3/XPZ2030GL	3	XPZ	2030	79.92	1.10	0.50
3/XPZ2120GL	3	XPZ	2120	83.46	1.15	0.52
3/XPZ2160GL	3	XPZ	2160	85.04	1.17	0.53
3/XPZ2240GL	3	XPZ	2240	88.19	1.22	0.55
3/XPZ2360GL	3	XPZ	2360	92.91	1.28	0.58
3/XPZ2500GL	3	XPZ	2500	98.43	1.36	0.62
3/XPZ2650GL	3	XPZ	2650	104.33	1.44	0.65
3/XPZ2800GL	3	XPZ	2800	110.24	1.52	0.69
4/XPZ800GL	4	XPZ	800	31.50	0.58	0.26
4/XPZ850GL	4	XPZ	850	33.46	0.62	0.28
4/XPZ900GL	4	XPZ	900	35.43	0.65	0.30
4/XPZ950GL	4	XPZ	950	37.40	0.69	0.31
4/XPZ1000GL	4	XPZ	1000	39.37	0.72	0.33
4/XPZ1030GL	4	XPZ	1030	40.55	0.75	0.34
4/XPZ1060GL	4	XPZ	1060	41.73	0.77	0.35
4/XPZ1090GL	4	XPZ	1090	42.91	0.79	0.36
4/XPZ1120GL	4	XPZ	1120	44.09	0.81	0.37
4/XPZ1150GL	4	XPZ	1150	45.28	0.83	0.38
4/XPZ1180GL	4	XPZ	1180	46.46	0.85	0.39
4/XPZ1212GL	4	XPZ	1212	47.72	0.88	0.40
4/XPZ1250GL	4	XPZ	1250	49.21	0.91	0.41
4/XPZ1270GL	4	XPZ	1270	50.00	0.92	0.42
4/XPZ1320GL	4	XPZ	1320	51.97	0.96	0.43
4/XPZ1340GL	4	XPZ	1340	52.76	0.97	0.44
4/XPZ1362GL	4	XPZ	1362	53.62	0.99	0.45
4/XPZ1400GL	4	XPZ	1400	55.12	1.01	0.46
4/XPZ1420GL	4	XPZ	1420	55.91	1.03	0.47
4/XPZ1450GL	4	XPZ	1450	57.09	1.05	0.48
4/XPZ1487GL	4	XPZ	1487	58.54	1.08	0.49
4/XPZ1500GL	4	XPZ	1500	59.06	1.09	0.49



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/XPZ1550GL	4	XPZ	1550	61.02	1.12	0.51
4/XPZ1600GL	4	XPZ	1600	62.99	1.16	0.53
4/XPZ1650GL	4	XPZ	1650	64.96	1.20	0.54
4/XPZ1700GL	4	XPZ	1700	66.93	1.23	0.56
4/XPZ1750GL	4	XPZ	1750	68.90	1.27	0.58
4/XPZ1800GL	4	XPZ	1800	70.87	1.30	0.59
4/XPZ1850GL	4	XPZ	1850	72.83	1.34	0.61
4/XPZ1900GL	4	XPZ	1900	74.80	1.38	0.62
4/XPZ1950GL	4	XPZ	1950	76.77	1.41	0.64
4/XPZ2000GL	4	XPZ	2000	78.74	1.45	0.66
4/XPZ2030GL	4	XPZ	2030	79.92	1.47	0.67
4/XPZ2120GL	4	XPZ	2120	83.46	1.54	0.70
4/XPZ2160GL	4	XPZ	2160	85.04	1.56	0.71
4/XPZ2240GL	4	XPZ	2240	88.19	1.62	0.74
4/XPZ2360GL	4	XPZ	2360	92.91	1.71	0.78
4/XPZ2500GL	4	XPZ	2500	98.43	1.81	0.82
4/XPZ2650GL	4	XPZ	2650	104.33	1.92	0.87
4/XPZ2800GL	4	XPZ	2800	110.24	2.03	0.92
5/XPZ800GL	5	XPZ	800	31.50	0.72	0.33
5/XPZ850GL	5	XPZ	850	33.46	0.77	0.35
5/XPZ900GL	5	XPZ	900	35.43	0.81	0.37
5/XPZ950GL	5	XPZ	950	37.40	0.86	0.39
5/XPZ1000GL	5	XPZ	1000	39.37	0.91	0.41
5/XPZ1030GL	5	XPZ	1030	40.55	0.93	0.42
5/XPZ1060GL	5	XPZ	1060	41.73	0.96	0.44
5/XPZ1090GL	5	XPZ	1090	42.91	0.99	0.45
5/XPZ1120GL	5	XPZ	1120	44.09	1.01	0.46
5/XPZ1150GL	5	XPZ	1150	45.28	1.04	0.47
5/XPZ1180GL	5	XPZ	1180	46.46	1.07	0.48
5/XPZ1212GL	5	XPZ	1212	47.72	1.10	0.50
5/XPZ1250GL	5	XPZ	1250	49.21	1.13	0.51
5/XPZ1270GL	5	XPZ	1270	50.00	1.15	0.52
5/XPZ1320GL	5	XPZ	1320	51.97	1.20	0.54
5/XPZ1340GL	5	XPZ	1340	52.76	1.21	0.55



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
5/XPZ1362GL	5	XPZ	1362	53.62	1.23	0.56
5/XPZ1400GL	5	XPZ	1400	55.12	1.27	0.58
5/XPZ1420GL	5	XPZ	1420	55.91	1.29	0.58
5/XPZ1450GL	5	XPZ	1450	57.09	1.31	0.60
5/XPZ1487GL	5	XPZ	1487	58.54	1.35	0.61
5/XPZ1500GL	5	XPZ	1500	59.06	1.36	0.62
5/XPZ1550GL	5	XPZ	1550	61.02	1.40	0.64
5/XPZ1600GL	5	XPZ	1600	62.99	1.45	0.66
5/XPZ1650GL	5	XPZ	1650	64.96	1.49	0.68
5/XPZ1700GL	5	XPZ	1700	66.93	1.54	0.70
5/XPZ1750GL	5	XPZ	1750	68.90	1.58	0.72
5/XPZ1800GL	5	XPZ	1800	70.87	1.63	0.74
5/XPZ1850GL	5	XPZ	1850	72.83	1.68	0.76
5/XPZ1900GL	5	XPZ	1900	74.80	1.72	0.78
5/XPZ1950GL	5	XPZ	1950	76.77	1.77	0.80
5/XPZ2000GL	5	XPZ	2000	78.74	1.81	0.82
5/XPZ2030GL	5	XPZ	2030	79.92	1.84	0.83
5/XPZ2120GL	5	XPZ	2120	83.46	1.92	0.87
5/XPZ2160GL	5	XPZ	2160	85.04	1.96	0.89
5/XPZ2240GL	5	XPZ	2240	88.19	2.03	0.92
5/XPZ2360GL	5	XPZ	2360	92.91	2.14	0.97
5/XPZ2500GL	5	XPZ	2500	98.43	2.26	1.03
5/XPZ2650GL	5	XPZ	2650	104.33	2.40	1.09
5/XPZ2800GL	5	XPZ	2800	110.24	2.54	1.15
6/XPZ800GL	6	XPZ	800	31.50	0.87	0.39
6/XPZ850GL	6	XPZ	850	33.46	0.92	0.42
6/XPZ900GL	6	XPZ	900	35.43	0.98	0.44
6/XPZ950GL	6	XPZ	950	37.40	1.03	0.47
6/XPZ1000GL	6	XPZ	1000	39.37	1.09	0.49
6/XPZ1030GL	6	XPZ	1030	40.55	1.12	0.51
6/XPZ1060GL	6	XPZ	1060	41.73	1.15	0.52
6/XPZ1090GL	6	XPZ	1090	42.91	1.18	0.54
6/XPZ1120GL	6	XPZ	1120	44.09	1.22	0.55
6/XPZ1150GL	6	XPZ	1150	45.28	1.25	0.57



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
6/XPZ1180GL	6	XPZ	1180	46.46	1.28	0.58
6/XPZ1212GL	6	XPZ	1212	47.72	1.32	0.60
6/XPZ1250GL	6	XPZ	1250	49.21	1.36	0.62
6/XPZ1270GL	6	XPZ	1270	50.00	1.38	0.63
6/XPZ1320GL	6	XPZ	1320	51.97	1.43	0.65
6/XPZ1340GL	6	XPZ	1340	52.76	1.46	0.66
6/XPZ1362GL	6	XPZ	1362	53.62	1.48	0.67
6/XPZ1400GL	6	XPZ	1400	55.12	1.52	0.69
6/XPZ1420GL	6	XPZ	1420	55.91	1.54	0.70
6/XPZ1450GL	6	XPZ	1450	57.09	1.58	0.71
6/XPZ1487GL	6	XPZ	1487	58.54	1.62	0.73
6/XPZ1500GL	6	XPZ	1500	59.06	1.63	0.74
6/XPZ1550GL	6	XPZ	1550	61.02	1.68	0.76
6/XPZ1600GL	6	XPZ	1600	62.99	1.74	0.79
6/XPZ1650GL	6	XPZ	1650	64.96	1.79	0.81
6/XPZ1700GL	6	XPZ	1700	66.93	1.85	0.84
6/XPZ1750GL	6	XPZ	1750	68.90	1.90	0.86
6/XPZ1800GL	6	XPZ	1800	70.87	1.96	0.89
6/XPZ1850GL	6	XPZ	1850	72.83	2.01	0.91
6/XPZ1900GL	6	XPZ	1900	74.80	2.06	0.94
6/XPZ1950GL	6	XPZ	1950	76.77	2.12	0.96
6/XPZ2000GL	6	XPZ	2000	78.74	2.17	0.99
6/XPZ2030GL	6	XPZ	2030	79.92	2.21	1.00
6/XPZ2120GL	6	XPZ	2120	83.46	2.30	1.04
6/XPZ2160GL	6	XPZ	2160	85.04	2.35	1.06
6/XPZ2240GL	6	XPZ	2240	88.19	2.43	1.10
6/XPZ2360GL	6	XPZ	2360	92.91	2.56	1.16
6/XPZ2500GL	6	XPZ	2500	98.43	2.72	1.23
6/XPZ2650GL	6	XPZ	2650	104.33	2.88	1.31
6/XPZ2800GL	6	XPZ	2800	110.24	3.04	1.38
2/XPA800GL	2	XPA	800	31.50	0.47	0.22
2/XPA850GL	2	XPA	850	33.46	0.50	0.23
2/XPA900GL	2	XPA	900	35.43	0.53	0.24
2/XPA950GL	2	XPA	950	37.40	0.56	0.26



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/XPA1000GL	2	XPA	1000	39.37	0.59	0.27
2/XPA1030GL	2	XPA	1030	40.55	0.61	0.28
2/XPA1060GL	2	XPA	1060	41.73	0.63	0.29
2/XPA1090GL	2	XPA	1090	42.91	0.65	0.29
2/XPA1120GL	2	XPA	1120	44.09	0.66	0.30
2/XPA1150GL	2	XPA	1150	45.28	0.68	0.31
2/XPA1180GL	2	XPA	1180	46.46	0.70	0.32
2/XPA1250GL	2	XPA	1250	49.21	0.74	0.34
2/XPA1320GL	2	XPA	1320	51.97	0.78	0.35
2/XPA1360GL	2	XPA	1360	53.54	0.81	0.37
2/XPA1400GL	2	XPA	1400	55.12	0.83	0.38
2/XPA1450GL	2	XPA	1450	57.09	0.86	0.39
2/XPA1500GL	2	XPA	1500	59.06	0.89	0.40
2/XPA1550GL	2	XPA	1550	61.02	0.92	0.42
2/XPA1600GL	2	XPA	1600	62.99	0.95	0.43
2/XPA1650GL	2	XPA	1650	64.96	0.98	0.44
2/XPA1700GL	2	XPA	1700	66.93	1.01	0.46
2/XPA1750GL	2	XPA	1750	68.90	1.04	0.47
2/XPA1800GL	2	XPA	1800	70.87	1.07	0.48
2/XPA1850GL	2	XPA	1850	72.83	1.10	0.50
2/XPA1900GL	2	XPA	1900	74.80	1.13	0.51
2/XPA1950GL	2	XPA	1950	76.77	1.16	0.52
2/XPA2000GL	2	XPA	2000	78.74	1.19	0.54
2/XPA2060GL	2	XPA	2060	81.10	1.22	0.55
2/XPA2120GL	2	XPA	2120	83.46	1.26	0.57
2/XPA2240GL	2	XPA	2240	88.19	1.33	0.60
2/XPA2360GL	2	XPA	2360	92.91	1.40	0.63
2/XPA2430GL	2	XPA	2430	95.67	1.44	0.65
2/XPA2500GL	2	XPA	2500	98.43	1.48	0.67
2/XPA2650GL	2	XPA	2650	104.33	1.57	0.71
2/XPA2800GL	2	XPA	2800	110.24	1.66	0.75
3/XPA800GL	3	XPA	800	31.50	0.71	0.32
3/XPA850GL	3	XPA	850	33.46	0.76	0.34
3/XPA900GL	3	XPA	900	35.43	0.80	0.36



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL®

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/XPA950GL	3	XPA	950	37.40	0.84	0.38
3/XPA1000GL	3	XPA	1000	39.37	0.89	0.40
3/XPA1030GL	3	XPA	1030	40.55	0.92	0.42
3/XPA1060GL	3	XPA	1060	41.73	0.94	0.43
3/XPA1090GL	3	XPA	1090	42.91	0.97	0.44
3/XPA1120GL	3	XPA	1120	44.09	1.00	0.45
3/XPA1150GL	3	XPA	1150	45.28	1.02	0.46
3/XPA1180GL	3	XPA	1180	46.46	1.05	0.48
3/XPA1250GL	3	XPA	1250	49.21	1.11	0.50
3/XPA1320GL	3	XPA	1320	51.97	1.17	0.53
3/XPA1360GL	3	XPA	1360	53.54	1.21	0.55
3/XPA1400GL	3	XPA	1400	55.12	1.24	0.56
3/XPA1450GL	3	XPA	1450	57.09	1.29	0.58
3/XPA1500GL	3	XPA	1500	59.06	1.33	0.61
3/XPA1550GL	3	XPA	1550	61.02	1.38	0.63
3/XPA1600GL	3	XPA	1600	62.99	1.42	0.65
3/XPA1650GL	3	XPA	1650	64.96	1.47	0.67
3/XPA1700GL	3	XPA	1700	66.93	1.51	0.69
3/XPA1750GL	3	XPA	1750	68.90	1.56	0.71
3/XPA1800GL	3	XPA	1800	70.87	1.60	0.73
3/XPA1850GL	3	XPA	1850	72.83	1.65	0.75
3/XPA1900GL	3	XPA	1900	74.80	1.69	0.77
3/XPA1950GL	3	XPA	1950	76.77	1.73	0.79
3/XPA2000GL	3	XPA	2000	78.74	1.78	0.81
3/XPA2060GL	3	XPA	2060	81.10	1.83	0.83
3/XPA2120GL	3	XPA	2120	83.46	1.89	0.86
3/XPA2240GL	3	XPA	2240	88.19	1.99	0.90
3/XPA2360GL	3	XPA	2360	92.91	2.10	0.95
3/XPA2430GL	3	XPA	2430	95.67	2.16	0.98
3/XPA2500GL	3	XPA	2500	98.43	2.22	1.01
3/XPA2650GL	3	XPA	2650	104.33	2.36	1.07
3/XPA2800GL	3	XPA	2800	110.24	2.49	1.13
4/XPA800GL	4	XPA	800	31.50	0.95	0.43
4/XPA850GL	4	XPA	850	33.46	1.01	0.46



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/XPA900GL	4	XPA	900	35.43	1.07	0.48
4/XPA950GL	4	XPA	950	37.40	1.13	0.51
4/XPA1000GL	4	XPA	1000	39.37	1.19	0.54
4/XPA1030GL	4	XPA	1030	40.55	1.22	0.55
4/XPA1060GL	4	XPA	1060	41.73	1.26	0.57
4/XPA1090GL	4	XPA	1090	42.91	1.29	0.59
4/XPA1120GL	4	XPA	1120	44.09	1.33	0.60
4/XPA1150GL	4	XPA	1150	45.28	1.36	0.62
4/XPA1180GL	4	XPA	1180	46.46	1.40	0.63
4/XPA1250GL	4	XPA	1250	49.21	1.48	0.67
4/XPA1320GL	4	XPA	1320	51.97	1.56	0.71
4/XPA1360GL	4	XPA	1360	53.54	1.61	0.73
4/XPA1400GL	4	XPA	1400	55.12	1.66	0.75
4/XPA1450GL	4	XPA	1450	57.09	1.72	0.78
4/XPA1500GL	4	XPA	1500	59.06	1.78	0.81
4/XPA1550GL	4	XPA	1550	61.02	1.84	0.83
4/XPA1600GL	4	XPA	1600	62.99	1.90	0.86
4/XPA1650GL	4	XPA	1650	64.96	1.96	0.89
4/XPA1700GL	4	XPA	1700	66.93	2.02	0.91
4/XPA1750GL	4	XPA	1750	68.90	2.07	0.94
4/XPA1800GL	4	XPA	1800	70.87	2.13	0.97
4/XPA1850GL	4	XPA	1850	72.83	2.19	0.99
4/XPA1900GL	4	XPA	1900	74.80	2.25	1.02
4/XPA1950GL	4	XPA	1950	76.77	2.31	1.05
4/XPA2000GL	4	XPA	2000	78.74	2.37	1.08
4/XPA2060GL	4	XPA	2060	81.10	2.44	1.11
4/XPA2120GL	4	XPA	2120	83.46	2.51	1.14
4/XPA2240GL	4	XPA	2240	88.19	2.66	1.20
4/XPA2360GL	4	XPA	2360	92.91	2.80	1.27
4/XPA2430GL	4	XPA	2430	95.67	2.88	1.31
4/XPA2500GL	4	XPA	2500	98.43	2.96	1.34
4/XPA2650GL	4	XPA	2650	104.33	3.14	1.43
4/XPA2800GL	4	XPA	2800	110.24	3.32	1.51
2/XPB1250GL	2	XPB	1250	49.21	1.24	0.56



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/XPB1320GL	2	XPB	1320	51.97	1.31	0.59
2/XPB1400GL	2	XPB	1400	55.12	1.38	0.63
2/XPB1450GL	2	XPB	1450	57.09	1.43	0.65
2/XPB1500GL	2	XPB	1500	59.06	1.48	0.67
2/XPB1550GL	2	XPB	1550	61.02	1.53	0.70
2/XPB1600GL	2	XPB	1600	62.99	1.58	0.72
2/XPB1650GL	2	XPB	1650	64.96	1.63	0.74
2/XPB1700GL	2	XPB	1700	66.93	1.68	0.76
2/XPB1750GL	2	XPB	1750	68.90	1.73	0.79
2/XPB1800GL	2	XPB	1800	70.87	1.78	0.81
2/XPB1850GL	2	XPB	1850	72.83	1.83	0.83
2/XPB1900GL	2	XPB	1900	74.80	1.88	0.85
2/XPB1950GL	2	XPB	1950	76.77	1.93	0.87
2/XPB2000GL	2	XPB	2000	78.74	1.98	0.90
2/XPB2120GL	2	XPB	2120	83.46	2.10	0.95
2/XPB2150GL	2	XPB	2150	84.65	2.13	0.96
2/XPB2240GL	2	XPB	2240	88.19	2.22	1.00
2/XPB2280GL	2	XPB	2280	89.76	2.26	1.02
2/XPB2360GL	2	XPB	2360	92.91	2.33	1.06
2/XPB2410GL	2	XPB	2410	94.88	2.38	1.08
2/XPB2500GL	2	XPB	2500	98.43	2.47	1.12
2/XPB2530GL	2	XPB	2530	99.61	2.50	1.14
2/XPB2650GL	2	XPB	2650	104.33	2.62	1.19
2/XPB2680GL	2	XPB	2680	105.51	2.65	1.20
2/XPB2800GL	2	XPB	2800	110.24	2.77	1.26
2/XPB2840GL	2	XPB	2840	111.81	2.81	1.27
3/XPB1250GL	3	XPB	1250	49.21	1.85	0.84
3/XPB1320GL	3	XPB	1320	51.97	1.96	0.89
3/XPB1400GL	3	XPB	1400	55.12	2.08	0.94
3/XPB1450GL	3	XPB	1450	57.09	2.15	0.98
3/XPB1500GL	3	XPB	1500	59.06	2.23	1.01
3/XPB1550GL	3	XPB	1550	61.02	2.30	1.04
3/XPB1600GL	3	XPB	1600	62.99	2.37	1.08
3/XPB1650GL	3	XPB	1650	64.96	2.45	1.11



MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL

Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part #	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/XPB1700GL	3	XPB	1700	66.93	2.52	1.14
3/XPB1750GL	3	XPB	1750	68.90	2.60	1.18
3/XPB1800GL	3	XPB	1800	70.87	2.67	1.21
3/XPB1850GL	3	XPB	1850	72.83	2.74	1.24
3/XPB1900GL	3	XPB	1900	74.80	2.82	1.28
3/XPB1950GL	3	XPB	1950	76.77	2.89	1.31
3/XPB2000GL	3	XPB	2000	78.74	2.97	1.35
3/XPB2120GL	3	XPB	2120	83.46	3.15	1.43
3/XPB2150GL	3	XPB	2150	84.65	3.19	1.45
3/XPB2240GL	3	XPB	2240	88.19	3.32	1.51
3/XPB2280GL	3	XPB	2280	89.76	3.38	1.53
3/XPB2360GL	3	XPB	2360	92.91	3.50	1.59
3/XPB2410GL	3	XPB	2410	94.88	3.58	1.62
3/XPB2500GL	3	XPB	2500	98.43	3.71	1.68
3/XPB2530GL	3	XPB	2530	99.61	3.75	1.70
3/XPB2650GL	3	XPB	2650	104.33	3.93	1.78
3/XPB2680GL	3	XPB	2680	105.51	3.98	1.80
3/XPB2800GL	3	XPB	2800	110.24	4.15	1.88
3/XPB2840GL	3	XPB	2840	111.81	4.21	1.91

PRODUCT STORAGE AND HANDLING CONDITIONS

- If possible, store in a cool, dry environment with no direct sunlight
- Ideal temperature for storage conditions is below 86°F (30°C)
- Avoid moisture, solvents or chemical contamination
- Continuous exposure to high temperatures such as 122°F (50°C) might significantly reduce belt life
- Humidity is not significantly causing issues
- If properly stored, belt shelf life is at least 5 years
- Short belts up to 59" (1.5 meters) can be stored on pegs
- Long belts should be coiled on shelves to prevent distortion

